

ISSN 2410-3950

Volume 8, Issue 24 — January — June - 2021

Journal of Experimental Systems

ECORFAN[®]

ECORFAN-Bolivia

Chief Editor

BARRERO-ROSALES, José Luis. PhD

Executive Director

RAMOS-ESCAMILLA, María. PhD

Editorial Director

PERALTA-CASTRO, Enrique. MsC

Web Designer

ESCAMILLA-BOUCHAN, Imelda. PhD

Web Diagrammer

LUNA-SOTO, Vladimir. PhD

Editorial Assistant

SORIANO-VELASCO, Jesús. BsC

Translator

DÍAZ-OCAMPO, Javier. BsC

Philologist

RAMOS-ARANCIBIA, Alejandra. BsC

Journal of Experimental Systems, Volume 8, Issue 24, January – June 2021, is a journal edited sixmonthly by ECORFAN-Bolivia. Loa 1179, Cd. Sucre. Chuquisaca, Bolivia. WEB: www.ecorfan.org/bolivia, journal@ecorfan.org. Editor in Chief: VALDIVIA - BARRERO-ROSALES, José Luis. PhD. ISSN On line: 2410-3950. Responsible for the latest update of this number ECORFAN Computer Unit. ESCAMILLA-BOUCHÁN, Imelda. PhD, LUNA-SOTO, Vladimir. PhD, last updated June 30, 2021.

The opinions expressed by the authors do not necessarily reflect the views of the editor of the publication.

It is strictly forbidden to reproduce any part of the contents and images of the publication without permission of the National Institute of Copyrigh

Journal of Experimental Systems

Definition of Research Journal

Scientific Objectives

Support the international scientific community in its written production Science, Technology and Innovation in the Field of Biology and Chemistry, in Subdisciplines Logical Methods, Research methods, Hypothetical-deductive method, Scientific observation method, Measuring method, Scientific experimentation, Climatology, Geology, Geochemistry, Acoustics.

ECORFAN-Mexico SC is a Scientific and Technological Company in contribution to the Human Resource training focused on the continuity in the critical analysis of International Research and is attached to CONACYT-RENIICYT number 1702902, its commitment is to disseminate research and contributions of the International Scientific Community, academic institutions, agencies and entities of the public and private sectors and contribute to the linking of researchers who carry out scientific activities, technological developments and training of specialized human resources with governments, companies and social organizations.

Encourage the interlocution of the International Scientific Community with other Study Centers in Mexico and abroad and promote a wide incorporation of academics, specialists and researchers to the publication in Science Structures of Autonomous Universities - State Public Universities - Federal IES - Polytechnic Universities - Technological Universities - Federal Technological Institutes - Normal Schools - Decentralized Technological Institutes - Intercultural Universities - S & T Councils - CONACYT Research Centers.

Scope, Coverage and Audience

Journal of Experimental Systems is a Research Journal edited by ECORFAN-Mexico S.C in its Holding with repository in Bolivia, is a scientific publication arbitrated and indexed with semester periods. It supports a wide range of contents that are evaluated by academic peers by the Double-Blind method, around subjects related to the theory and practice Logical Methods, Research methods, Hypothetical-deductive method, Scientific observation method, Measuring method, Scientific experimentation, Climatology, Geology, Geochemistry, Acoustics with diverse approaches and perspectives , That contribute to the diffusion of the development of Science Technology and Innovation that allow the arguments related to the decision making and influence in the formulation of international policies in the Field of Biology and Chemistry. The editorial horizon of ECORFAN-Mexico® extends beyond the academy and integrates other segments of research and analysis outside the scope, as long as they meet the requirements of rigorous argumentative and scientific, as well as addressing issues of general and current interest of the International Scientific Society.

Editorial Board

CARVAJAL - MILLAN, Elizabeth. PhD
École Nationale Supérieure Agronomique de Montpellier

CÓRDOVA - GUERRERO, Iván. PhD
Universidad de la Laguna

ARMADO - MATUTE, Arnaldo José. PhD
Universidad de los Andes

RIVERA - BECERRIL, Facundo. PhD
Institut National de la Recherche Agronomique

CRUZ - REYES, Juan. PhD
Instituto de Catálisis y Petroleoquímica

LOPEZ - ZAMORA, Leticia. PhD
Universidad Politécnica de Valencia

STILIANOVA - STOYTCHEVA, Margarita. PhD
Universidad de Tecnología Química y Metalurgia de Sofia

CORNEJO - BRAVO, José Manuel. PhD
University of California

SOTERO - SOLIS, Victor Erasmo. PhD
Universidade de São Paulo

OROPEZA - GUZMÁN, Mercedes Teresita. PhD
National Polytechnique de Toulouse

Arbitration Committee

ALVARADO - FLORES, Jesús. PhD
Universidad Autónoma de Aguascalientes

DE LEON - FLORES, Aneel. PhD
Universidad Nacional Autónoma de México

MARTÍNEZ - QUIROZ, Marisela. PhD
Centro de Investigación y Desarrollo Tecnológico en Electroquímica

MAGANA - BADILLA, Héctor Alfonso. PhD
Universidad Autónoma de Baja California

VALDEZ - CASTRO, Ricardo. PhD
Universidad Nacional Autónoma de México

QUIROZ - CASTILLO, Jesús Manuel. PhD
Universidad de Sonora

SANTACRUZ - ORTEGA, Hisila del Carmen. PhD
Instituto Tecnológico de Tijuana

MENDOZA - CASTILLO, Didilia Ileana. PhD
Instituto Tecnológico de Aguascalientes

OCHOA - TERÁN, Adrián. PhD
Tecnológico Nacional de México

FRONTANA - VAZQUEZ, Carlos Eduardo. PhD
Universidad Autónoma Metropolitana

SALDARRIAGA, Hugo. PhD
Universidad Autónoma del Estado de México

Assignment of Rights

The sending of an Article to Journal of Experimental Systems emanates the commitment of the author not to submit it simultaneously to the consideration of other series publications for it must complement the Originality Format for its Article.

The authors sign the Authorization Format for their Article to be disseminated by means that ECORFAN-Mexico, S.C. In its Holding Bolivia considers pertinent for disclosure and diffusion of its Article its Rights of Work.

Declaration of Authorship

Indicate the Name of Author and Coauthors at most in the participation of the Article and indicate in extensive the Institutional Affiliation indicating the Department.

Identify the Name of Author and Coauthors at most with the CVU Scholarship Number-PNPC or SNI-CONACYT- Indicating the Researcher Level and their Google Scholar Profile to verify their Citation Level and H index.

Identify the Name of Author and Coauthors at most in the Science and Technology Profiles widely accepted by the International Scientific Community ORC ID - Researcher ID Thomson - arXiv Author ID - PubMed Author ID - Open ID respectively.

Indicate the contact for correspondence to the Author (Mail and Telephone) and indicate the Researcher who contributes as the first Author of the Article.

Plagiarism Detection

All Articles will be tested by plagiarism software PLAGSCAN if a plagiarism level is detected Positive will not be sent to arbitration and will be rescinded of the reception of the Article notifying the Authors responsible, claiming that academic plagiarism is criminalized in the Penal Code.

Arbitration Process

All Articles will be evaluated by academic peers by the Double Blind method, the Arbitration Approval is a requirement for the Editorial Board to make a final decision that will be final in all cases. MARVID® is a derivative brand of ECORFAN® specialized in providing the expert evaluators all of them with Doctorate degree and distinction of International Researchers in the respective Councils of Science and Technology the counterpart of CONACYT for the chapters of America-Europe-Asia- Africa and Oceania. The identification of the authorship should only appear on a first removable page, in order to ensure that the Arbitration process is anonymous and covers the following stages: Identification of the Research Journal with its author occupation rate - Identification of Authors and Coauthors - Detection of plagiarism PLAGSCAN - Review of Formats of Authorization and Originality-Allocation to the Editorial Board- Allocation of the pair of Expert Arbitrators-Notification of Arbitration -Declaration of observations to the Author-Verification of Article Modified for Editing-Publication.

Instructions for Scientific, Technological and Innovation Publication

Knowledge Area

The works must be unpublished and refer to topics of Logical Methods, Research methods, Hypothetical-deductive method, Scientific observation method, Measuring method, Scientific experimentation, Climatology, Geology, Geochemistry, Acoustics and other topics related to Biology and Chemistry.

Presentation of Content

In the first article we present, *Elaboration of Octagonal Roses to represent the wind patterns in the Port de Veracruz during the last 10 years*, by GONZALEZ-JUAREZ Aníbal, AGUILAR-RAMIREZ Ana María, UTRERA-ZARATE, Alberto and MOLINA-NAVARRO, Antonio, with adscription in the Instituto Oceanográfico del Pacífico, as next article we present, *Comparative study between Biological treatment and a physicochemical treatment for the removal of Butyl Acetate in industrial residual effluents*, by CARRILLO-CABRERA, Roxana, RODRIGUEZ-MORALES, Jose Alberto, LEDESMA-GARCIA, Janet and AMARO-REYES, Aldo, with adscription in the Universidad Autónoma de Querétaro, as next article we present, *Thermodynamic analysis of a combined gas-steam cycle without and with afterburner*, by CASADOS-LÓPEZ, Edzel Jair, CASADOS-SÁNCHEZ, Alvaro, ESCAMILLA-RODRÍGUEZ, Frumencio and CORTÉZ-DOMÍNGUEZ, Cristóbal, with adscription in the Universidad Veracruzana, as next article we present, *Rupture voltage in mineral oil using the megger OTS 60pb equipment to determine its quality and use in transformers*, by ESCAMILLA-RODRÍGUEZ, Frumencio, LAGUNA-CAMACHO, Juan Rodrigo, RÍOS-HERNÁNDEZ, Sara Anahí and JIMÉNEZ-CRISTÓBAL, Juan Daniel, with adscription in the Universidad Veracruzana.

Content

Article	Page
Elaboration of Octagonal Roses to represent the wind patterns in the Port de Veracruz during the last 10 years GONZALEZ-JUAREZ Aníbal, AGUILAR-RAMIREZ Ana María, UTRERA-ZARATE, Alberto and MOLINA-NAVARRO, Antonio <i>Instituto Oceanográfico del Pacífico</i>	1-8
Comparative study between Biological treatment and a physicochemical treatment for the removal of Butyl Acetate in industrial residual effluents CARRILLO-CABRERA, Roxana, RODRIGUEZ-MORALES, Jose Alberto, LEDESMA-GARCIA, Janet and AMARO-REYES, Aldo <i>Universidad Autónoma de Querétaro</i>	9-16
Thermodynamic analysis of a combined gas-steam cycle without and with afterburner CASADOS-LÓPEZ, Edzel Jair, CASADOS-SÁNCHEZ, Alvaro, ESCAMILLA-RODRÍGUEZ, Frumencio and CORTÉZ-DOMÍNGUEZ, Cristóbal <i>Universidad Veracruzana</i>	17-24
Rupture voltage in mineral oil using the megger OTS 60pb equipment to determine its quality and use in transformers ESCAMILLA-RODRÍGUEZ, Frumencio, LAGUNA-CAMACHO, Juan Rodrigo, RÍOS-HERNÁNDEZ, Sara Anahí and JIMÉNEZ-CRISTÓBAL, Juan Daniel <i>Universidad Veracruzana</i>	25-32

Elaboration of Octagonal Roses to represent the wind patterns in the Port de Veracruz during the last 10 years

Elaboración de Rosas Octagonales para representar el comportamiento del viento en el Puerto de Veracruz durante los últimos 10 años

GONZALEZ-JUAREZ Aníbal*†, AGUILAR-RAMIREZ Ana María, UTRERA-ZARATE, Alberto and MOLINA-NAVARRO, Antonio

Instituto Oceanográfico del Pacífico

ID 1st Author: *Aníbal, González-Juárez* / ORC ID: 0000-0002-7012-5277, CVU CONACYT ID: 1003848

ID 1st Co-author: *Ana María, Aguilar-Ramírez* / ORC ID: 0000-0003-2867-8254, CVU CONACYT ID: 811392

ID 2nd Co-author: *Alberto, Utrera-Zarate* / ORC ID: 0000-0002-6282-4449, CVU CONACYT ID: 365626

ID 3rd Co-author: *Antonio, Molina-Navarro* / ORC ID: 0000-0001-7949-8371, CVU CONACYT ID: 811437

DOI: 10.35429/JOES.2021.24.8.1.8

Received March 29, 2021; Accepted June 30, 2021

Abstract

The Port de Veracruz and its surroundings are affected by meteorological phenomena such as the passage of frontal systems, among others. The main objective of this writing is to carry out continuous monitoring to categorize wind behavior, in order to determine patterns in the last 10 years. Therefore, climatological records of the intensity and direction of the average wind speeds are presented; wind data from three Automatic Meteorological Surface Stations (EMAS) of the Meteorological Observation Network of the Secretariat of the Navy, one of the National Meteorological Service (SMN) and two buoys of the National Oceanic and Atmospheric Administration (NOAA) were processed and analyzed. The results indicated that the North (N) direction predominately governs during the cold front season, while the East (E) winds predominately govern during the warm months (June, July, August and September). The maximum gusts, which can be an important factor in accidents, especially when their intensity exceeds 20 knots, affect various human, maritime, agricultural and livestock activities and tourism.

Resumen

El puerto de Veracruz y sus inmediaciones se ven afectados por fenómenos meteorológicos como el paso de sistemas frontales, entre otros, el objetivo primordial del presente trabajo es efectuar la constante observación y evaluación para caracterizar el comportamiento del viento, con el fin de determinar la tendencia en los últimos 10 años. Por lo anterior, se presentan registros climatológicos de la intensidad y dirección del viento promedio; se procesaron y analizaron datos de viento provenientes de tres Estaciones Meteorológicas Automáticas de Superficie (EMAS) de la Red de Observación Meteorológica de la Secretaría de Marina, una del Servicio Meteorológico Nacional (SMN) y dos boyas de la Administración Nacional Oceánica y Atmosférica (NOAA). Los resultados indicaron que la dirección Norte (N) predomina durante la temporada de frentes fríos, mientras que los vientos del Este (E) lo hace durante los meses cálidos (junio, julio, agosto y septiembre). Las ráfagas máximas, que pueden constituir un factor importante de accidentes, especialmente cuando su intensidad supera los 20 nudos ya que afecta a diversas actividades humanas, marítimas, agropecuarias y turismo.

Octagonal roses, wind, wind power

Rosas octagonales, viento, energía eólica

Citación: GONZALEZ-JUAREZ Aníbal, AGUILAR-RAMIREZ Ana María, UTRERA-ZARATE, Alberto and MOLINA-NAVARRO, Antonio. Elaboration of Octagonal Roses to represent the wind patterns in the Port de Veracruz during the last 10 years. Journal of Experimental Systems. 2021. 8-24: 1-8

* Author Correspondence (anibal_goju@yahoo.com.mx).

† Researcher contributing as first author.

Introduction

Wind is the movement of air in any direction and its magnitude can vary from a calm state to very intense winds (Tai, 2015); it is considered one of the most relevant variables due to its importance in different economic sectors. Such as maritime energy to mention one example; as wind can exert considerable force on some structures, such that some shipping operators limit operations when winds exceed 15 to 20 knots due to the formation of wind waves and the discomfort of crew and passengers, as well as threats to their safety (WMO, 2018). High winds create hazardous working conditions for personnel on exposed decks and affect survey platforms, loading and unloading operations, helipad, module access and general deck operations (WMO, 2018). For this reason, safety and security in Mexican ports must be strengthened and legal certainty must be provided to the maritime community.

The port of Veracruz is the oldest port in Mexico and, historically, the most significant in the country due to its equipment for the transport of vehicles imported or exported by sea and the movement of container cargo (APIVER 2021). In addition to being the best connected of the nation, which allows supplying 15 states of the Mexican Republic, which serves more than 67 million inhabitants and also has maritime routes to more than 150 ports in the world. It is also responsible for generating 11% of the national electricity (Silva-Casari n et al., 2018) and represents 37% of the national territory (INEGI, 1988). This port and its surroundings are affected by meteorological phenomena such as the passage of frontal systems and tropical waves, which makes it necessary to constantly observe and evaluate the behaviour of the wind (Calder n, 2017).

In order to fulfil this purpose and given the lack of climate characterisation and the importance it has for the exploitation of the country's natural resources, this work proposes a study of the behaviour of winds in the Port of Veracruz over the last 10 years, considering the recommendations of the World Maritime Organisation, which suggests constant monitoring of climatological variables and their representation in the form of maps, graphs and statistics, given that they are useful for numerous activities, ranging from navigation to the planning of various operations on the coast.

In order to serve as a useful reference tool for both promoting favourable maritime development and sustainable exploitation of resources in this geographical area. On the other hand, it is relevant to carry out the study of wind behaviour in the port of Veracruz, in order to have a recent analysis with which to determine the wind trend in recent years; also complying with the WMO regulations in which it specifies about local studies, in order to observe its variability.

Methodology

In order to characterise the wind over the port of Veracruz, the meteorological stations closest to the port of Veracruz were identified, six in total, which are described in Table 1, located in Figure 1.

Station	Years	Period
Heroic Military Naval School (HENM)	10	2010-2019
Boca del Rio	9	2010-2018
Sacrificios	8	2012-2019
Oceanographic Institute of the Gulf and Caribbean Sea (IOGMC)	3	2016-2019
NOAA Buoy	6	2011-2016
NOAA Sacrificios	6	2011-2016

Table 1 Meteorological stations consulted
Source (Own Elaboration)



Figure 1 Location of stations used
Source: Google Maps

Using the Python programming language, the wind data were cleaned, creating time, speed and direction matrices, in order to homogenise them in terms of format and structure. Due to the fact that the winds recorded by the EMAS and the buoys are in time intervals of 15 min and 60 min, respectively, the following quality control actions were carried out to clean the database:

- Anomalous data were identified within each record and were taken as missing data
- Records indicating more than 30 days without data were considered as missing.
- Data where the sustained wind exceeded the gust were taken as erroneous data and were not used.

After the quality control actions and through descriptive statistics, the averages were obtained, identifying the dominant wind during the day. As the data recorded the direction in degrees, the components and their equivalence in degrees were identified in a wind rose. Working with the eight classical components and defining the intervals to have homogeneous directions.

Images were produced for a better interpretation of the information. These graphics were generated with the software Inkscape, which is a vector graphics editor, and with it, wind roses were made in an octagonal shape; thus obtaining the behaviour of the wind (direction and intensity) during the last 10 years in the port of Veracruz.

Results and analysis

The representation was carried out through octagonal shaped graphs, where each side of the geometric figure represents one of the wind components. Each of these sides is the base of a bar graph representing the monthly average wind frequency and the colour, based on the Beaufort scale, indicates the maximum average sustained wind that can be expected. Also, in the central part, it is shown if there was no wind, a situation known as calm periods.

Each of the images presented below has two support elements in the lower corners to be able to interpret them correctly, 1) lower right corner: shows the Beaufort scale in km/h (Table 2), with their respective colours according to the intensity, which are used in the bars on each side of the octagonal, to show the average maximum sustained wind, 2) lower left corner the reference scale of the percentage units.

Scale	Speed (km/h)	Designation	Colour	Designation Colour
0	0 – 1	calm		
1	1 to 5	Ventolina		Blue
2	5 to 11	Very weak breeze (weak)		Cyan
3	13 to 19	Light Breeze (Light)		Green
4	19 to 28	Moderate breeze (Bonancible)		Light Green
5	28 to 38	Fresh breeze (Fresquito)		Yellow-Green
6	38 to 49	Strong breeze (Fresco)		Yellow
7	49 to 61	Strong wind (Frescachón)		Orange
8	61 to 74	Hard Wind (Temporary)		Red-Orange
9	74 to 88	Strong wind (Very strong)		Red
10	88 to 102	Strong Storm (Temporal)		Purple
11	102 to 117	Very strong storm (Squall)		Dark Blue
12	+ 117	Hurricane storm (Hurricane)		Dark Blue

Table 2 BEAUFORT SCALE

Source: Directorate of Meteorology SEMAR

Figure 2 shows the percentage of wind direction for the data series 2010-2019. It should be noted that the HENM station is the most representative, as it presents the complete period during the 10 years.




Figure 2 Percentage of wind direction at HENM station
Source: Own Elaboration

In this station there is a variation in its wind regime, none of the 8 components reaches 50 % of predominance in the year. However, the dominant direction is from the N, with a frequency of 26.2% in the month of December. But this is followed by the NW and S components, with a percentage of 18% in the month of November and 29.8% in the month of July respectively.

In this EMA it is important to point out that the winds have a great variability in the wind direction, but always with a predominance of the N and S sector, since in the other quadrants they have frequencies below 15 %. Likewise, the prevailing wind direction in the last 10 years at HENM has been N.

The most notable characteristic in this place are the calms or air movement whose speed is zero or less than 2 knots, or what is the same as force 0 on the Beaufort scale, which shows that the month of May is the one with the lowest percentage of them with 0%; which indicates that throughout this month the wind is perceptible, regardless of the direction. For the rest of the months it ranges between 14.3% and 30.1%, with the sole exception of July, which is 33.9%, a circumstance that coincides with the fact that July is when the lowest wind intensity is recorded. The percentage of calms tends to increase when the secondary courses try to match the dominant ones.

Figure 3 shows the percentage of wind direction at the Boca del Río station during the 2010-2018 data period.




Figure 3 Percentage of wind direction at Boca del Río station

Source: Own Elaboration

It should be noted that this station is the second with the second highest number of real data. It shows an important incidence of winds coming from the North, followed by the Northeast and East.

From the month of September onwards, the winds from the N component persist in an ascending manner, being reflected in the month of November with maximum winds of 51.7 km/h and in a descending manner that continues until the month of May. The NE and E components have an impact in the months of June, July and August. Likewise, the prevailing wind direction in the last 10 years at the Boca del Río station is North.

Figure 4 shows the percentage of the wind direction of the station located in Isla de Sacrificios, for a period of observations 2012-2019. The most frequent direction is from the N, followed by the E.




Figure 4 Percentage of wind direction at the Isla de Sacrificios station

Source: Own Elaboration

The most frequent directions are from the N and E with a percentage of 37.6% in December and 41.9% in July respectively. Winds from the SE (11.8%) reached a notable frequency in December. The directions with a medium and low frequency are S (6.7%), SW (6.0%), W (8.3%) and NW (12.9%).

In terms of wind speed, it is observed that the wind has exceeded degree 7 on the Beaufort scale, classified as strong wind; it is recorded in January and December where winds reach 54.6 km/h and 57.1 km/hr respectively; with July and August being on the opposite side of the scale. There are no calm periods.

In this season, the season of frontal systems is fully manifested and is reflected in the intensity of its winds; on the other hand, the presence of easterly winds is appreciated both in percentage and intensity in the months of June, July and August. Likewise, the prevailing wind direction in the last 10 years at the Isla Sacrificios station has been from the N component.

Figure 5 shows the percentage of the wind direction of the station located in the IOGMC, for the period 2016-2019. It is important to point out that the data processing carried out at this station is not representative of a climatology; but in addition to this, an analysis was carried out in which the lack of data is very noticeable. However, they can be used to draw conclusions about the importance of the data and the action of the city, as this station is located in the urban centre.

But it stands out that the direction with the highest percentage is from the N and NE, with an average of 33.9 % in December and 53.8 % in July respectively. The calm periods are below 15 %, in the months of February, March, April and August. In terms of speed, the highest intensities are observed in December with 19 km/h. The lowest speeds are in December with 19 km/h. The lowest speeds are in the month of August.




Figure 5 Wind direction percentage of the IOGMC station
Source: Own Elaboration

In the analysis of this EMA, it is made clear that, given the lack of data, it is very difficult to characterise a variable; but this is not the objective of the study, which is why we do not go into detail regarding the characteristics of the station itself. However, the prevailing wind direction over the last 10 years at the IOMC station is NE.

Figure 6 shows the percentage of the NOAA Buoy wind direction in which there was wind by component, using all the observations for the period 2011-2016. The graph confirms, on the one hand, the dominance of N winds throughout the year, which reach their maximum percentage in the month of January; and on the other hand, winds from the Northeast and East as the second dominant component. The rest of the directions are considered secondary because they are below 20 %.




Figure 6 Percentage of wind direction at NOAA Buoy
Source: Own Elaboration

The directions with the highest frequency are N, NE and E with a percentage in December (50.0%), in July (38.7%) and May (32.6%) respectively. The directions with a low frequency are SE (3.2%), S (3.2%), SW (3.3%), W (3.2%), and NW (3.2%). At this station the wind speeds are observed to exceed degree 7 on the Beaufort scale (Table 2), classified as strong wind; it is recorded in November, December, January, April and May where the winds exceed 55 km/h. July is the month with the lowest wind intensity. Likewise, the prevailing wind direction over the last 10 years at the NOAA buoy is from the north.

Figure 7 shows the percentage of wind direction at the NOAA Sacrificios station, using data from 2011-2016. It can be seen that the most frequent direction is N during the winter months, which have the highest intensities with values between 49 and 74 km/h on average during that period; while the NE and E directions also occupy the second position, but unlike the first, these occur mostly during the summer months, as they are influenced by the trade winds. The percentage of calms is nil.




Figure 7 Percentage of wind direction at the NOAA Sacrificios station

Source: Own Elaboration

The most frequent directions are N and NE and E with a percentage in January (48.4%), in July (34.9%) and May (23.7%) respectively. Winds from the SE (17.2%) reached a notable frequency in December.

In terms of wind speed, it can be seen that the wind exceeds grade 8 on the Beaufort scale, classified as a hard wind; it is recorded in December (62.5 km/h); the months of October, November, January, February, March and April have winds of grade 7 on the Beaufort scale. Likewise, the prevailing wind direction in the last 10 years at the Sacrificios NOAA station is from the N component.

The percentages of calm winds are low and are below 3% in February, March, October and November. This buoy presents very similar data to EMA, which is located in Sacrificios Island.

Conclusions

Regarding the results obtained by studying the wind behaviour in the five stations and one buoy, it is evident to observe weak and moderate winds blowing in all directions in most months; although their percentages are very low, winds from the East and West are frequent; representing almost 50% in the stations of Boca del Río, Isla de Sacrificios, Isla de Sacrificios NOAA and Boya de la NOAA. This marked component is due to the local regime of sea breeze and continental breeze winds, which are present in synoptically stable conditions, as well as in the spring and summer seasons; which are the product of the difference in temperatures between the ocean-continent dichotomy, which cause pressure differences and consequently the wind that goes from high pressure to low pressure on surfaces.

In addition, during the months of June, July, August and September, it is observed that the easterly winds indicate a higher percentage and increase in wind speed, which means the possibility of the existence of a more accentuated sea breeze phenomenon over the area of the Port of Veracruz.

For the HENM, IOGC and Boca del Río stations, it is where the lowest wind intensities occurred, due to the fact that they are located within the urban area and the wind friction with the heterogeneities of the terrain, such as buildings, trees and small hills, causes the wind to decrease its speed or change its horizontal momentum flow to vertical.

Finally, the stations of Isla de Sacrificios, Isla de Sacrificios NOAA and the NOAA Buoy are where the wind registers the highest intensities (between 74 and 88 km/h), since these points are free of obstacles or barriers that diminish or deviate the intensity and direction of the wind, These intensities are present in the winter season with a northerly direction, which is considered the windiest season of the year, due to the air masses that move from polar areas towards the coast of the Gulf of Mexico (see figure 8).




Figure 8 Octagonal roses representing the stations in the study area

Source: Google maps base map

Recommendations

The analysis and creation of wind roses for a quick and complete description of the climatic wind situation at a weather station should be put into practice in academia.

The institutions responsible for climatological data should emphasise the importance of having time series as complete as possible, since the periodic maintenance of these stations translates into good data.

References

Acevedo Rosas, Federico, y Antonio Luna Díaz-Peón. 2005. “Principales Fenómenos Meteorológicos que afectaron al estado de Veracruz en el Año 2005.”

Ahmed, M. M. Ibtihaj Abbas. 2017. “Denominaciones Científicas y Populares de Los Vientos.”

OMM. 2018. Guía de Servicios Meteorológicos Marinos.

Arias Llanos, José, y Juan Cervantes Pérez. 1999. “Vientos Máximos En El Estado de Veracruz.”

Díaz, Carlos Garrido. 2002. “Predicción de Datos Faltantes en Red de Estaciones Climatológicas.”

Hernández-Escobedo, Quetzalcoatl, Francisco Espinosa-Arenal, Ricardo Saldaña-Flores, 2012. “Evaluación Del Potencial Eólico para la Generación de Energía Eléctrica en el Estado de Veracruz, México.” DYNA (Colombia) 79(171):215–21.

Instituto Nacional de Estadística y Geografía. (1988). Síntesis Geográfica. Anexo Cartográfico del Estado de Veracruz. (pp. 69). Instituto Nacional de Estadística, Geografía e Informática.

Magaña, Victor, Luis Jose Pérez, Vazquez Luis Jorge, Carrisoza Eliseo, y Pérez Joel. 1999. “El Niño y El Clima.” 23–68.

Mosiño, PA, E. García. 1974. “El Clima de México.” Londres: Elsevier 11:345–404.

Organización Mundial de Meteorología. 2011. Guía de Prácticas Climatológicas. Vol. 100.

Pérez, Luis Manuel Santana. 2019. “Estudio Meteorológico en el Centro Insular. El Comportamiento del Viento en Tenerife. Primera Parte.”

Román, A. N. A. Victoria. 2015. “Impactos sobre el Istmo Centroamericano”.

Secretaría de Protección Civil. 2017. “Calendario de Temporadas y Fenómenos Meteorológicos Para El Estado de Veracruz.” 1.

Silva-Casarín, R., Moreno-Casasola, P., Martínez, Ma. L., Mendoza Baldwin, E., López-Portillo, J., Lithgow, D., Vázquez, G., Martínez Martínez, R. E., Monroy Ibarra, R., Cáceres Puig, J. I., Ramírez Hernández, A., & Boy Tamborrell, M. (2018). La zona costera del estado del estado de Veracruz. clima marítimo, medio físico y medio biótico (1st ed., pp. 9–70). Instituto De Ecología.

Tai, Osorio Elena. 2015. “Estudio de La Intensificación de Los Vientos En El Puerto de Veracruz Mediante Modelación Numérica.” 10–12.

Tejeda- Martinez Adalberto, 2004. “Circulación Local y Ascenso de Aire en un Sitio Costero y Tropical al Pie de la Montaña.” Asociación Española de Climatología.

Zamudio, Alfredo Ruiz Barradas y Adalberto Tejeda Martínez S, 2015. "Climatología." *Anales de La Real Academia Nacional de Farmacia* 81(5):84–100.

Zeng, Zhenzhong. 2018. "Global Terrestrial Stilling." *Journal of Chemical Information and Modeling* 53(9):1689–99.

APIVER. n.d. "APIVER - Administración Portuaria Integral de Veracruz." Retrieved (<https://www.puertodeveracruz.com.mx/wordpress/blog/nuevo-record-2/>).

Comparative study between biological treatment and a physicochemical treatment for the removal of Butyl Acetate in industrial residual effluents

Estudio comparativo entre un tratamiento biológico y un tratamiento fisicoquímico para la remoción de Butil Acetato en efluentes residuales industriales

CARRILLO-CABRERA, Roxana^{1†}, RODRIGUEZ-MORALES, Jose Alberto^{*2}, LEDESMA-GARCIA, Janet² and AMARO-REYES, Aldo¹

¹Facultad de Química de la Universidad Autónoma de Querétaro.

²Facultad de Ingeniería de la Universidad Autónoma de Querétaro

ID 1st Author: Roxana, Carrillo-Cabrera / ORC ID: 0000-0003-2068-0835, CVU CONACYT ID: 248405

ID 1st Co-author: Jose Alberto, Rodriguez-Morales / ORC ID: 0000 0002-4532-9665, CVU CONACYT ID: 200320

ID 2nd Co-author: Janet, Ledesma-Garcia / ORC ID: 0000 0002-0677-4280, CVU CONACYT ID: 104183

ID 3rd Co-author: Aldo, Amaro-Reyes / ORC ID: 0000 0001- 6520-5742, CVU CONACYT ID: 222109

DOI: 10.35429/JOES.2021.24.8.9.16

Received: March 30, 2021; Accepted June 30, 2021

Abstract

A comparison was made between a fixed aerobic biological process and a physicochemical treatment for waste effluents with butyl acetate. An acrylic tank with 100 L capacity and a support medium for PET bottles was implemented for the formation of the biofilm and thus develop the biological reactor. In the experimental phase, concentrations of 10, 20 and 30% of butyl acetate containing sample, using hydraulic retention times of: (16, 8, 5.33 and 4 days) for each concentration. After the experimentation, a removal of 99% of COD and 97% of BOD was obtained. For the physicochemical treatment, coagulant, flocculant, and adjuvants were used, by a jar test. A decrease in 74%, 53.8%, 55%, 97% and 37%, for electrical conductivity, total suspended solids, color, turbidity, COD and BOD respectively, were obtained compared to the initial sample. Both treatments were filtered through a bed packed with activated carbon, sand, and silica gravel. The aim of this work was to evaluate / quantify butyl acetate removal efficiency in each treatment for its subsequent comparison, with prospect to the reduction of similar pollutants in residual effluents is intended.

Biological treatment, Physicochemical treatment, Butyl acetate

Resumen

Se realizó una comparación entre un proceso biológico aerobio fijo y un tratamiento fisicoquímico para efluentes residuales con butil acetato. Para el desarrollo del reactor biológico se implementó un tanque de acrílico con capacidad de 100 L y un medio de soporte de botellas PET para la formación del biofilm, en la parte experimental se manejaron concentraciones de 10, 20 y 30 % de la muestra con butil acetato, empleando tiempos de retención hidráulica de: (16, 8, 5.33 y 4 días) para cada concentración. Finalizada la experimentación se obtuvo una remoción del 99% de DQO y 97 % de DBO. Para el tratamiento fisicoquímico se empleó coagulante, floculante y coadyuvantes, mediante una prueba de jarras. Obteniendo como resultados la disminución en un 74 %, 53.8 %, 55 %, 97 % y 37%, para conductividad eléctrica, sólidos suspendidos totales, color, turbidez, DQO y DBO respectivamente, en comparación a la muestra inicial. Ambos tratamientos se filtraron mediante un lecho empacado con carbón activado, arena y grava sílica. El objetivo del presente trabajo fue evaluar/cuantificar la eficiencia de remoción del butil acetato en cada tratamiento para su posterior comparación, por lo cual se pretende la reducción de contaminantes similares en efluentes residuales.

Tratamiento biológico, Tratamiento fisicoquímico, Butil acetato

Citation: CARRILLO-CABRERA, Roxana, RODRIGUEZ-MORALES, Jose Alberto, LEDESMA-GARCIA, Janet and AMARO-REYES, Aldo. Comparative study between Biological treatment and a physicochemical treatment for the removal of Butyl Acetate in industrial residual effluents. Journal of Experimental Systems. 2021. 8-24: 9-16

* Author Correspondence (josealberto970@hotmail.com)

† Researcher contributing as first author.

Introducción

Surface water and groundwater pollution is reported at 24% and 4% respectively, which has been generated by high concentrations of various chemical species. These come from diffuse sources of pollution (use of pesticides, manure production in agriculture) and specific sources (industrial landfills, as well as in industrial mining practices).

Effluents from industrial processes contain toxic products, harmful organic compounds, and metals, of varying composition, type and concentration, depending on the processes that generate them. Natural organic compounds in the environment tend to naturally degrade slowly into less harmful components, however, volatile organic compounds (VOCs) found in effluents from industrial processes are not considered biodegradable.

VOCs are used in the manufacture of paints, varnishes, waxes and are chemical industry's main organic pollutants used as solvents, being butyl acetate ($C_6H_{12}O_2$), most widely used, as a solvent in polyurethane resins and paints (stripping) for special applications. It is a colorless liquid with a fruity odor, soluble in organic solvents, highly flammable, and dangerous to health, affecting the central nervous system.

It has been reported in various studies that water contaminated with compounds like butyl acetate, such as ethyl tert-butyl ether ($C_6H_{14}O$), methyl tert-butyl ether ($C_5H_{12}O$), tert-amyl methyl ether ($C_6H_{14}O$) and diisopropyl ether ($C_6H_{14}O$), have been treated by using microorganisms in a biodegradation process. Because it is a slow process, the addition of specific bacteria selected for their efficiency in removing contaminants has been implemented.

Residual water

Wastewater can be classified according to its origin: industrial, commercial, and domestic sector, in some cases adequate treatments are not implemented for its reuse, which, depending on current regulations and the economic interest of each company, is the importance given to the treatment process.

The pollutants concentration present in wastewater varied according to the origin of the sample and industrial use, suspended solids, organic matter, oils, fats, nitrogen, and phosphorus can be found. Membrane activated carbon filtration and chemical precipitation techniques are the most used for its recovery.

Types of wastewater treatment

The treatments most used in wastewater purification processes are primary, secondary, and tertiary, the conditions, on which, the choice of a treatment is based are the flow rate to treat, the concentration of pollutants, the type of pollutants, the place weather and the continuity in the raw water supply, the treatments are described below:




Figure 1 General water treatment diagram
Own Elaboration

Another treatment is disinfection, which consists of eliminating or inactivating pathogenic microorganisms or any other living microorganism to ensure the reuse of treated water. The main disinfection processes are chlorination, ozonation, electro-disinfection.

Methodology Reactor development

A 100 L capacity acrylic tank was used, with the following dimensions (60 cm x 56 cm x 30 cm), which was adapted as a reactor. Two valves were placed after the feed inlet, a sphere type with a diameter of 1.5 inches, flow 3.95 L sec^{-1} , to regulate the feed flow of the affluent through the upper and lower part of the reactor.

To regulate the effluent outflow and the biomass purge, two ball valves were used as previously described. The sludge was recirculated with a MAXIMA® aeration pump for 113.6 L, which were connected to three 45 cm long porous rubber diffuser hoses, fish tank type to maintain a dissolved oxygen concentration of 3-4 mg L⁻¹ arranged at the bottom of the tank.

Support medium

108 polyethylene terephthalate (PET) bottles of different capacities (2, 1 and 0.5 L) with holes were used to facilitate air flow. They were placed concentrically (they were assembled from smaller to larger capacity) and were distributed in an organized way in the bioreactor to allow the flow of the water, thus avoiding the obstruction of this, to increase the contact surface and the development of the biofilm, such as can be seen in Figure 2.



Figure 2 Fixed aerobic biological reactor prototype

Biological process development

For the formation of the biofilm in the reactor, 3 L of activated sludge inoculum from the treatment plant of the Autonomous University of Querétaro, Airport campus, were used. The sludge was fed with residual water from the same plant of the institution collected from laboratories and bathrooms, for a period of 1 to 6 months for maintenance, adaptation, and formation of biofilm in the PET support, as observed in Figure 3.



Figure 3 Biofilm formation

After establishing the biofilm and being able to guarantee the efficiency of the system in reducing nutrients, BOD / COD degradation and pH stabilization, the effluent quality analysis was carried out to verify compliance with NOM-003-ECOL-1997 and NOM-001-SEMARNAT-96.

Biokinetic coefficients

To evaluate the efficiency of the reactor and the stabilization of the biomass, the biokinetic coefficients were determined (Equation 1), which indicate the growth of the biomass, the use rate of the substrate, the food-microorganism relationship, and the mean time of cell retention. Equation to calculate the mean speed constant (K_s).

$$\frac{\theta X}{S_0 - S} = \frac{K_s}{(k)(S)} + \frac{1}{k} \quad (1)$$

Where:

θ = hydraulic retention time (h)

X = concentration of volatile suspended solids in the mixed liquor, L / h, mg VSS ML / L / h

S_0 = concentration of soluble COD in influent (mg L⁻¹)

S = concentration of soluble COD in effluent (mg L⁻¹)

k = maximum substrate utilization rate (h)

K_s = mean speed constant (mg L⁻¹)

Equation 2 to calculate maximum cell yield (Y) and endogenous decay coefficient (k_d)

$$\frac{1}{\theta_c} = Y \frac{S_0 - S}{X\theta} - k_d \quad (2)$$

Where:

Y = maximum cell yield

k_d = endogenous decay coefficient, h⁻¹

Subsequently, contaminant elimination from the test sample was sought using microorganisms adapted to the residual water in the reactor in a period of 1 to 6 months.

Calculation of the contact area of the biofilm

To calculate the contact area of the microorganisms to the PET support, the following equations were used for the truncated cone (3) and cylinder (4):

$$A = \pi(R_1^2 + R_2^2 + a(R_1 + R_2)) \quad (3)$$

$$A_c = b \times h = (2\pi r)(h) \quad (4)$$

Adaptation of the effluent aerobic biological process (ABP) with butyl acetate

For the beginning of this adaptation stage, it was carried out by adding the effluent with butyl acetate to the biological reactor. Three concentrations were used (10, 20 and 30%) diluted in residual water, the process was carried out for four months, as shown in Figure 4 and 5.



Figure 4 Biological reactor feeding with domestic wastewater and effluent with butyl acetate mixture



Figure 5 Biological reactor adaptation to the effluent with butyl acetate

Hydraulic retention times

The different hydraulic retention times applied were 16, 8, 5.33 and 4 days for each of the concentrations used (10, 20 and 30%) of wastewater and effluent with butyl acetate.

Development of the physicochemical process

For the physicochemical process, 10 experiments were carried out using the jar test for the coagulant, flocculant, and adjuvants, which were carried out on a shaker (PHIPPS & BIRD, USA), for testing 6-place jars with six 1 L beakers, the stirring time was 5 min at 150 rpm. The initial pH of the samples was 3.6.

Table 1 summarizes the methodology applied, as well as the concentrations used in the reagents to perform the jar tests.

Test	Conditions
1	pH 3.6-9, 45 ml chemical lime (20%), 5 ml metal precipitator (1%), 2 ml coagulant 90/10 (10%), 5 ml flocculant 70/24 (1%)
2	pH 3.6-2, 1.8 ml of H ₂ SO ₄ (98%), 2 ml metal precipitator (1%), pH 7, 45 ml chemical lime (20%), 2.5 ml coagulant 90/10 (10%), 1.3 ml flocculant 70/24 (1%)
3	pH 3.6- 6, 30 ml chemical lime (20%), 3 ml metal precipitator (1%), 1.5 ml coagulant 90/10 (10%), 2 ml flocculant 70/24 (1%)
4	pH 3.6- 8, 40 ml chemical lime (20%), 7 ml metal precipitator (1%), 4 ml coagulant 90/10 (10%), 7 ml flocculant 70/24 (1%)
5	pH 3.6-1, 2.8 ml H ₂ SO ₄ (98%), 3 ml metal precipitator (1%), pH 7, 60 ml chemical lime (20%), 2 ml coagulant 90/10 (10%), 8 ml of flocculant 70/24 (1%)

Table 1 Conditions applied at jar tests

Filtration system

A 60 cm acrylic column and a diameter of 10 cm was run. It was packed with activated carbon, sand, and silica gravel 1-1 ½ cm, using layers of 15 cm of each, the result obtained is shown in Figure 6.



Figure 6 Physicochemically treated sample before and after filtration

The samples after the biological and physicochemical treatment were subjected to a filtration process and the result is shown in Figure 7.



Figure 7 Filtered samples after biological treatment (1, 2 and 3) and physicochemical treatment (4)

Analytical techniques

The analyzes of pH, conductivity, chemical oxygen demand (COD), total dissolved solids (TDS), total solids (ST) and color (Pt-Co), were applied for both treatments.

Results

Biological treatment: Domestic wastewater characterization

Parameter	Value obtained	Maximum allowable limit
Temperature °C	25.5	40 °C
Fats and Oils	25	25 mg/L
Floating Matter	Ausente	Ausente
Settling Solids	3	2 mg/L
Total Suspended Solids	500	60 mg/L
Biochemical Oxygen Demand	600	60 mg/L
Total Nitrogen	50	25 mg/L
Total Phosphorous	20	10 mg/L
Arsenic	N.D.	0.2 mg/L
Cadmium	N.D.	0.2 mg/L
Cianide	N.D.	2.0 mg/L
Copper	N.D.	6.0 mg/L
Chromium	N.D.	1.00 mg/L
Mercury	N.D.	0.01 mg/L
Níckel	N.D.	4.0 mg/L
Lead	N.D.	0.4 mg/L
Zinc	N.D.	20 mg/L

Table 2 Characterization of NOM-001 SEMARNAT 1996

Parameter	Value obtained	Maximum allowable limit
Fecal coliforms	≥ 2400000 NMP	240 NMP/100 ml
Helmith eggs	< 1	< 1 (h/1)
Fats and oils	25	15 m/l
BOD ₅	594	20 mg/l
TSS	500	20 mg/l

Table 3 Characterization of NOM-003 SEMARNAT 1997

Biokinetic constant

Obtaining the Chemical Oxygen Demand (S) and Volatile Suspended Solids (X), associated with the calculation of the biokinetic coefficients, shown in Table 4.

Cycle	S ₀	S	$\theta = \theta_c$	X
	g/L COD	g/L COD	h	g VSS/L
1	0.795	--	0	5.00
2	--	0.284	1	4.86
3	--	0.176	2	4.53
4	--	0.154	4	3.5
5	--	0.138	8	2.30

Table 4 Chemical Oxygen Demand (S) and Volatile Suspended Solids (X)

To obtain the maximum substrate utilization rate (k) and the average speed constant (Ks), the data obtained from Table 5 was first plotted with calculations of the equation Y.

X0 g VSS/h*L	1 / S (h) ⁻¹	X0/(S ₀ - S) h ⁻¹
4.86	3.533	9.0005
9.06	5.6818	14.3711
14	6.4935	16.4003
18.4	7.2463	18.2825

Table 5 Variables associated with the calculation of k and Ks




Figure 8 Maximum growth rate (k) and Average growth rate (Ks)

Figure 8 is the graph of $X_0 / (S_0 - S)$ according to $1 / S$. In this graph the ordinate to the origin is $1 / k$, and the slope is equal to K_s / k . Thus, obtaining k and Ks were 5.91 h^{-1} and 14.78 g / L respectively.

Maximum cell yield (Y) and endogenous decay coefficient (kd)

The variables $1 / \theta_c$ and $(S_0 - S) / X_0$ were obtained based on the data shown in table 6. The graph of these results to obtain the biokinetic coefficients: Maximum cell yield (Y) and the endogenous decay coefficient (kd) is shown in Figure 9.

$1/\theta_c$ h ⁻¹	$(S_0 - S) / X_0$ h ⁻¹
1	0.112
0.5	0.067
0.25	0.048
0.125	0.037

Table 6 Variables associated with the calculation of Y and Kd




Figure 9 Maximum cell yield (Y) and endogenous decay coefficient (kd)

Coefficients	Result obtained
Substrate utilization rate (k) g CODs / gVSS	5.91
Average rate constant (Ks) mg / l CODs	14.78
Maximum cell yield (Y) mg VSS / mg CODs	0.085
Endogenous decay coefficient (kd) g SSV / g VSS	0.025

Table 7 Results obtained from the biokinetic coefficients of the biological reactor

Once $1 / \theta_c$ was graphed with respect to $(S_0 - S) / X_0$, the ordinate to the origin kd was obtained and the slope is Y. Consequently, the values of Y and kd that were obtained were 0.085 and 0.025 h^{-1} respectively.

Biofilm formation

The sum of the area of the truncated cone and the cylinder resulted in 0.604262 m^2 and the total contact area of the system for the reactor was 10.272454 m^2 .

Hydraulic retention

The parameters established in NOM 003 SEMARNAT 1997 were analyzed for the different hydraulic retention times in each concentration, as shown in Table 8 (a, b and c).

Holding time (days)	COD (mg/L)	BOD (mg/L)	TSS (mg/L)	Fats and oils (mg/L)	Fecal coliforms (NMP/100 ml)	Helminth Eggs (Organismos/L)
16	16	12.90	9	<1.0	<3.0	Absent
8	14	14.32	12	<1.0	<3.0	Absent
5.33	18	17.56	15	<1.0	<3.0	Absent
4	19	18.7	14	<1.0	<3.0	Absent
Maximum allowable	N.E.	20	20	15	240	<1.0

Table 8 a 10 % concentration

Holding time (days)	COD (mg/L)	BOD (mg/L)	TSS (mg/L)	Fats and oils (mg/L)	Fecal coliforms (NMP/100 ml)	Helminth Eggs (Organismos/L)
16	16	18.49	13	<1.0	<3.0	Absent
8	19	19.16	12	<1.0	<3.0	Absent
5.33	15.51	19.38	13	<1.0	<3.0	Absent
4	18.51	21.45	12	<1.0	<3.0	Absent
Maximum allowable	N.E.	20	20	15	240	<1.0

Table 8 b 20 % concentration

Holding time (days)	COD (mg/L)	BOD (mg/L)	TSS (mg/L)	Fats and oils (mg/L)	Fecal coliforms (NMP/100 ml)	Helminth Eggs (Organismos/L)
16	19	14.4	12	<1.0	<3.0	Absent
8	10	12.75	10	<1.0	<3.0	Absent
5.33	15	16.23	11	<1.0	<3.0	Absent
4	19	19.62	14	<1.0	<3.0	Absent
Maximum allowable	N.E.	20	20	15	240	<1.0

Table 8 c 30 % concentration

Physicochemical treatment

The results are shown in Table 9, of the parameters characterized before and after the physicochemical treatment.

Parameter	Unit	Initial result	Final result
Electric conductivity	μS	13925	7298
Total suspended solids	mg/L	1390	360
Color	Pt-Co	934	432
Turbidity	NTU	756	340
COD	mg/L	35720	959
BOD	mg/L	900	300
pH	N/A	3.2	7

Table 9 Industrial wastewater characterization

Conclusions

Physicochemical treatment

The parameters analyzed after treatment were decreased by 74%, 53.8%, 55%, 97% and 67%, for electrical conductivity, total suspended solids, color, turbidity, COD and BOD respectively, compared to the initial sample.

Biological treatment

The parameters analyzed in the different hydraulic retention times in the experimental part for COD was 99%. As well as they also present the values of BOD 97%, for all the values. Regarding compliance with NOM 003 SEMARNAT 1997, all retention times comply except for the retention time of 3.2 days for the 30% concentration with wastewater and effluent with butyl acetate

In both treatments there was COD reduction, which indicates that there is a significant removal percentage for butyl acetate. The comparison of the treatments applied to the effluent showed that the biological treatment presented greater removal of the pollutant before the physicochemical treatment in 2% of COD and 30% of BOD.

Discussion

A mass coupled gas spectroscopy analysis is recommended to confirm the removal of butyl acetate in the effluent or the transformation into other chemical species.

References

Adin A., Rebhun M. 1974. High-rate contact flocculation-filtration with cationic polyelectrolytes. *Journal American water Works association*. 66(2).

Arboleda, J. 2000. *Teoría y práctica de la purificación del agua*, tercera edición (Tomo. I), McGraw-Hill.

Bartling, J., Esperschütz, J., Wilke, B., Schloterb, M. 2011. ETBE (ethyl tert butyl ether) and TAME (tert amyl methyl ether) affect microbial community structure and function in soils. *Journal of Hazardous Materials*. 187 (1-3) 488–494.

Burguete M. Y. (2016). *Acoplamiento de un sistema biológico aerobio y un proceso avanzado de oxidación para el tratamiento de un efluente acuoso*, (Tesis Maestría en Ciencia y Tecnología Ambiental). Universidad Autónoma de Querétaro. México. 72p

Castellani, B., Morini, E., Filippini, M., Nicolini, A., Palombo, M., Cotana, F., Rossi, F. 2014. Comparative analysis of monitoring devices for particulate content in exhaust gases. *Sustainability*. 6(7): 4287–4307.

Cleasby, J. 1969. Approaches to a filterability index for granular filters. *Journal American Water Works Association*. 61(8):372.

Comisión Nacional del Medio Ambiente (CONAMA). 1998. *Política ambiental para el desarrollo sustentable*, Chile.

Davis, M. 2010. *Water and wastewater engineering: Design principles and practice*. <https://www.accessengineeringlibrary.com/content/book/9780071713849>

González, M. (2015). *División de un sedimentador*. <http://www.tratamientodelagua.com.mx/teoria-de-sedimentacion/>

Hernández, M., Gonzáles, N. 1993. Recursos hídricos y ambiente. En: *Elementos de política ambiental*. Cámara de Diputados de la Provincia de Buenos Aires, Argentina. Pg. 175-184.

Kirk, R., Othmer, D., Grayson, M., Eckroth, D. 1981. *Kirk-Othmer Encyclopedia of Chemical Technology*, 3rd ed.; John Wiley: New York, NY, USA, p. 664.

Kobe, K. 1958. Unit Processes in Organic Syntheses (Groggins, P. H.). *Journal of Chemical Education*. 35(11):584.

Manahan, S. 2011. *Introducción a la química ambiental*. Editorial Revérte, UNAM. México. Pág. 36-42, 172-173, 205-214, 217-218, 228-230.

Mastroianni, N., López-García, E., Postigo, C., Barceló, D., López de Alda, M. 2017. Five-year monitoring of 19 illicit and legal substances of abuse at the inlet of a wastewater treatment plant in Barcelona (NE Spain) and estimation of drug consumption patterns and trends. *Science of The Total Environment*. 609:916–926.

Mendoza, B. 2016. Acoplamiento de un sistema biológico aerobio a un proceso avanzado de oxidación para el tratamiento de un efluente acuoso. Tesis de maestría. Universidad Autónoma de Querétaro. México.

Metcalf, L., Eddy, H. 2003. *Ingeniería de aguas residuales*. Editorial McGraw-Hill. 53-59.

Metcalf y Eddy. 1995. *Ingeniería de las aguas residuales* (vol. I), Madrid: McGraw-Hill.

Mihelcic, J., Zimmerman, J. 2011. *Ingeniería ambiental. Fundamentos, sustentabilidad, diseño*. Editorial Alfaomega. Pg. 65-85, 310-322.

Nolasco, T., 2013. Cinética de crecimiento celular: Ecuación de Monod. [En línea] Universidad Autónoma del Estado de México, 2003. [Citado el: 11 de 11 de 2016.] <http://es.slideshare.net/edya69/ecuacin-de-monod-copia>.

Norma Oficial Mexicana NOM-001-SEMARNAT-1996, que establece los límites máximos permisibles de contaminantes en las descargas de aguas residuales en aguas y bienes nacionales.

<https://www.profepa.gob.mx/innovaportal/file/3290/1/nom-001-semarnat-1996.pdf>

Norma Oficial Mexicana NOM-003-SEMARNAT-1997, que establece los límites máximos permisibles de contaminantes para las aguas residuales tratadas que se reúsen en servicios al público. https://www.gob.mx/cms/uploads/attachment/file/110523/NOM_003_SEMARNAT_1997.pdf

The national Institute for occupational safety and health (NIOSH). 2019. *Pocket Guide to Chemical Hazards*.

Thornton, F., Nicholls, G., Rolfe, A., Mallinson, H., Spence, J. 2020. Biodegradation and fate of ethyl tert-butyl ether (ETBE) in soil and groundwater: A review. *Journal of Hazardous Materials*. 391:122046

Tuset, S. 2018. Sistemas con reactores aeróbicos para tratar aguas residuales. *Condorchem Envitech Smart ideas for wastewater and air treatment*.

Thermodynamic analysis of a combined gas-steam cycle without and with afterburner

Análisis termodinámico de un ciclo combinado gas-vapor sin y con Postcombustión

CASADOS-LÓPEZ, Edzel Jair†*, CASADOS-SÁNCHEZ, Alvaro, ESCAMILLA-RODRÍGUEZ, Frumencio and CORTÉZ-DOMÍNGUEZ, Cristóbal

Universidad Veracruzana, Facultad de Ingeniería Mecánica Eléctrica, Campus Poza Rica – Tuxpan, Veracruz, México.

ID 1st Author: *Edzel Jair, Casados-López* / ORC ID: 0000-0002-0601-9242

ID 1st Coauthor: *Alvaro, Casados-Sánchez* / ORC ID: 0000-0002-3122-4571

ID 2nd Coauthor: *Frumencio, Escamilla-Rodríguez* / ORC ID: 0000-0002-5075-1924 / CVU CONACYT ID: 1134105

ID 3rd Coauthor: *Cristóbal, Cortez-Domínguez* / ORC ID: 0000-0002-5720-4405 / CVU CONACYT ID: 972957

DOI: 10.35429/JOES.2021.24.8.17.24

Received 09 March, 2021; Accepted 28 June, 2021

Abstract

Currently in power plants what is sought are higher thermal efficiencies, which is why combined cycle plants have been chosen, since they make better use of fuel, producing greater net power, all this It has led to innovative modifications to combined cycle power plants, improving their performance. In this article the thermodynamic analysis of a combined cycle (Gas-Steam) without and with Afterburner is carried out, in said analysis adequate thermodynamic indices have been used and the calculations have been carried out taking into account the state of the art for gas turbines and the typical values for steam cycle quantities. The purpose of this study is to analyze the combined plants where the exhaust gas at the outlet of the gas turbine is used in a waste heat recovery boiler to produce steam that is expanded in a turbine and discharged in a condenser. Since the air-fuel ratio in the combustion chamber of a gas turbine is higher than the stoichiometric, fuel can be added in the boiler (Afterburner) to increase steam production or to improve the quality of the steam produced.

Combined cycle plant (Gas–Steam), Afterburner, Recovery boiler

Resumen

En la actualidad en las plantas de energía lo que se busca son eficiencias térmicas más altas, es por lo que se ha optado por las centrales de ciclo combinado, ya que en ellas se aprovecha mejor el combustible, produciendo una mayor potencia neta, todo esto ha originado modificaciones innovadoras en las centrales de ciclo combinado, mejorando el rendimiento de este. En este artículo se lleva a cabo el análisis termodinámico de un ciclo combinado (Gas-Vapor) sin y con Postcombustión, en dicho análisis han sido utilizados índices termodinámicos adecuados y los cálculos se han realizado teniendo en cuenta el estado del arte para turbinas de gas y los valores habituales para las cantidades de los ciclos de vapor. El propósito de este estudio es analizar las plantas combinadas donde el gas de escape a la salida de la turbina de gas es utilizado en una caldera de recuperación de calor residual para producir vapor que es expandido en una turbina y descargado en un condensador. Ya que la relación aire–combustible en la cámara de combustión de una turbina de gas es mayor al estequiométrico, se puede añadir combustible en la caldera (Postcombustión) para aumentar la producción de vapor o para mejorar la calidad del vapor producido.

Ciclo combinado (Gas-Vapor), Postcombustión, Caldera de recuperación

Citation: CASADOS-LÓPEZ, Edzel Jair, CASADOS-SÁNCHEZ, Alvaro, ESCAMILLA-RODRÍGUEZ, Frumencio and CORTÉZ-DOMÍNGUEZ, Cristóbal. Thermodynamic analysis of a combined gas-steam cycle without and with afterburner. Journal of Experimental Systems. 2021. 8-24: 17-24

* Correspondence to Author (Email: torlia@hotmail.com).

†Researcher contributing as first Author.

Introduction

Man has a natural tendency to try to improve the efficiency of devices in converting thermal energy into mechanical work. Moreover, the rising costs of fossil fuels as well as the care of the environment is a stimulus for this type of research. Power plants where gas turbines, operating in open cycle, are combined with steam cycles, are of particular interest because of their high conversion efficiency. The combination of these two types of cycles is possible due to the high temperature heat in the turbine exhaust, which depends on the ratio of gas temperature and maximum pressure. For many years the focus of manufacturers and utilities has been on combined cycles (Gas-Steam). Many combinations are possible and gas turbines, in addition to generating mechanical power, can perform different tasks according to their position in the plants.

Pfenninger analysed a plant in which the maximum gas temperature was $T_{3a} = 880\text{ }^{\circ}\text{C}$ and concluded that the gas turbine cycle must have the maximum exhaust enthalpy (i.e. the maximum product between the mass flow of the gas and its temperature). The resulting pressure ratio was intermediate between these for which the gas turbine specific work and efficiency are maximum. The afterburner was taken into consideration and the conclusions were that for a low afterburner rate the efficiency decreases slightly, then a maximum is reached in the ratio between gas turbine power and total plant power. An excess of air comprises this ratio.

The total output went up with minimal excess air in the exhaust gas. Wunsch, stated that the efficiency of a combined gas-steam plant is mostly influenced by the gas turbine parameters (T_{3a} , β) what by the steam cycles, the parameters were set in an appropriate way. The conclusion was that the maximum efficiency of the combined Gas-Steam cycle was reached when the exhaust temperature of the gas turbine was higher than the corresponding maximum efficiency of the gas turbine. In the same study the afterburner was taken into consideration and its influence was positive when the maximum gas turbine temperature was lower than 950°C and negative for higher temperatures.

In the present study, a thermodynamic analysis of a combined Gas-Steam cycle is carried out, with one pressure level, with no regeneration drawdowns. The results of the parametric analysis of the cycle performance are given.

Nomenclature

T = Temperature

P = Pressure

V = Volume

C_p = Specific heat at constant pressure

kP = Pressure loss coefficient

h = Enthalpy

pc = Pressure in the condenser in Mpa.

q = Ratio of heat in the afterburner to heat in the combustion chamber and the heat in the combustion chamber of the combustion chamber of the gas turbine

s = Entropy

S = Mass ratio air - vapour

T_{6a} , t_{6a} = Temperature at discharge, $^{\circ}\text{C}$, K

T_c , t_c = Condenser temperature, $^{\circ}\text{C}$, K

x = Steam quality at the outlet of the steam turbine steam turbine outlet steam quality

\dot{W} = Work, KJ

Q = Heat, KJ

W_o = Specific work, KJ/Kg

α = Air-fuel mass ratio

α_{st} = Stoichiometric air-fuel mass ratio

β_{gt} = Pressure ratio of gas turbine

β_{st} = Steam turbine pressure ratio

Γ_i = Net heat output KJ/Kg

ϵ_b = Steam generator efficiency

Y = Fraction of compressed air for cooling of blades and accessories.

$V_s = R/C_p$ = Ratio of gas constant to specific heat constant at constant pressure in the transformation.

W_n = Net work

W_{gt} = Work of the gas turbine

W_{st} = Work of steam turbine

CC = Combined Cycle

WCC = Net combined cycle work

QS = Heat supplied

η_{gt} = Thermal efficiency of the gas turbine

η_{st} = Thermal efficiency of steam turbine steam turbine thermal efficiency

η_{CC} = Thermal efficiency of combined cycle

The schematic diagram of the simple gas-steam combined cycle is presented below.




Figure 1 Schematic diagram of the simple combined gas-steam cycle

Source: Own Elaboration

In the following, the thermodynamic calculations of the simple combined cycle are presented, whose reference was taken from the: Cerri, G., (1987) Parametric analysis of combined gas - steam cycles. Journal of Engineering for Gas Turbines and Power, vol. 109, pag. 46 - 54.

Compression

$$T_{2a} = (T_1)(\beta^{va12/\eta_{pc}}) \quad (1)$$

$$T_{2a} = (305 \text{ K})(14^{0.285/0.85})$$

$$T_{2a} = 738.91 \text{ K}$$

Taking into account the friction of the compressed air to cool the blades and accessories.

$$Y = 0.05 \quad \text{sí} \quad T_{3a} \leq 1273 \text{ K}$$

sí:

$$T_{3a} \geq 1273 \text{ K}$$

$$Y = \frac{0.05(T_{3a} - 273)}{1000} \quad (2)$$

$$Y = \frac{0.05(1536 - 273)}{1000}$$

$$Y = 0.06315$$

The work absorbed by the compressor is:

$$W_c = \frac{C_{pa1-2}}{\eta_{mc}} (T_{2a} - T_1)(1 + Y) \quad (3)$$

$$W_c = \frac{1.005}{0.98} (738.91 - 305)(1 + 0.06315)$$

$$W_c = 473.08 \text{ KJ/Kg}$$

Gas Turbine Combustion

The energy balance of the combustion chamber is:

$$\frac{\Gamma \eta_{bgt}}{\alpha_{gt}} = \left(1 + \frac{1}{\alpha_{gt}}\right) C_{pa2-3} (T_{3a} - T_{2a}) \quad (4)$$

The air-fuel ratio is:

$$\alpha_{gt} = \frac{\Gamma \eta_{bgt}}{C_{pa2-3} (T_{3a} - T_{2a})} - 1$$

$$\alpha_{gt} = \frac{48490 (0.98)}{1.0838(1536 - 738.91)} - 1$$

$$\alpha_{gt} = 54.0$$

Heat Supplied

$$Q_s = \frac{\Gamma \eta_{bgt}}{\alpha_{gt}} \quad (5)$$

$$Q_s = \frac{(48490)(0.98)}{54.0}$$

$$Q_s = 880 \text{ KJ/Kg}$$

Expansion in the gas turbine

$$\beta_{gt} = k_p \beta_c \quad (6)$$

$$\beta_{gt} = (0.9238)(14) = 12.9332$$

$$K_p = \frac{\left(1 - \frac{\Delta p_{2a}}{P_{2a}}\right)}{\left(1 + \frac{\Delta p_{4a}}{P_{4a}}\right)} \quad (7)$$

$$K_p = \frac{0.97}{1.05} = 0.9238$$

$$T_{4a} = \frac{T_3}{\beta_{gt}^{va34\eta_{pgt}}} \quad (8)$$

$$T_{4a} = \frac{1536}{12.9332^{((0.2366)(0.8837))}} = \frac{1536}{1.7074}$$

$$T_{4a} = 899 \text{ K}$$

$$W_{gt} = \left(1 + \frac{1}{\alpha_{gt}}\right) C_{pa3-4} (T_3 - T_{4a}) \eta_{mgt} \quad (9)$$

$$W_{gt} = \left(1 + \frac{1}{54}\right) 1.2136 (1536 - 899) 0.98$$

$$W_{gt} = 770.88 \text{ KJ/Kg}$$

$$\eta_{gt} = \frac{770.88 - 473.08}{800} = 0.3384 = 33.84 \%$$

The enthalpy of steam at the boiler outlet is:

$$H_{3s} = H(T_{3s}, p_{2s}) \quad (10)$$

$$T_{3s} = 523 \text{ °C} = 796 \text{ K}$$

$$P_{2s} = 7.742 \text{ Mpa}$$

$$H_{3s} = 3457.87 \text{ KJ/Kg}$$

The enthalpy of the condenser feed water is:

$$h_c = h(p_c) \quad (11)$$

$$p_c = 8.91 \text{ kpa}$$

$$h_c = 182.46 \text{ KJ/Kg}$$

The energy balance in the generator can be expressed as:

$$(1 + \frac{1}{\alpha}) C_{pa4-6}(T_{4a} - T_{6a})\epsilon_b = S(H_{3s} - h_c)$$

$$C_{pa4-6} = 1.12 \text{ KJ Kg/K}$$

$$T_{4a} = 899.61 \text{ K}$$

$$T_{6a} = 363.6 \text{ K}$$

$$\epsilon_b = 0.96$$

By subtracting the vapour-air mass ratio (S)

$$S = \frac{(1 + \frac{1}{\alpha}) C_{pa4-6}(T_{4a} - T_{6a})\epsilon_b}{(H_{3s} - h_c)} \quad (12)$$

$$S = 0.1878$$

The work of steam expansion

The adiabatic efficiency of the steam turbine expansion can be expressed by P_{2s} and P_c and the polytropic efficiency. As:

$$\beta_{st} = \frac{P_{2s}}{P_c} \quad (13)$$

$$\beta_{st} = \frac{7742 \text{ kpa}}{8.91 \text{ kpa}}$$

$$\beta_{st} = 868.91$$

$$\eta_{ast} = \frac{\beta_{st}^{Vs\eta_{pst}} - 1}{\beta_{st}^{Vs} - 1} \beta_{st}^{Vs(1 - \eta_{pst})} \quad (14)$$

$$\eta_{ast} = 0.9365$$

The entropy of the steam at the turbine inlet is:

$$s_{3s} = s(T_{3s}, p_{2s}) \quad (15)$$

$$s_{3s} = 6.8149 \text{ KJ Kg / K}$$

Quality at the turbine outlet:

$$x = \frac{6.8149 - 0.61515}{7.5821} = 0.8176$$

$$H_{cs} = H(S_{3s}, p_c) \quad (16)$$

$$H_{cs} = H_f + x H_{fg}$$

$$H_{cs} = 2143.88 \text{ KJ/Kg}$$

$$\eta_{tv} = \frac{H_{3s} - h_{4s}}{H_{3s} - H_{cs}} \quad (17)$$

$$h_{4s} = 2227.32 \text{ KJ/Kg}$$

Steam turbine work:

$$W_{st} = s(H_{3s} - h_{4s})\eta_{ast}\eta_{mst} \quad (18)$$

$$W_{st} = 212.09 \text{ KJ/Kg}$$

Heat supplied:

$$Q_s = s(H_{3s} - h_c) \quad (19)$$

$$Q_s = 615.12 \text{ KJ/Kg}$$

Thermal efficiency of the steam turbine:

$$\eta_{st} = \frac{W_{st}}{Q_s} \quad (20)$$

$$\eta_{st} = 0.3448 = 34.48 \%$$

The schematic diagram of the combined gas-steam cycle with afterburner is shown below.




Figure 2 Schematic diagram of the combined gas-steam cycle with afterburner
Source: Cerri




Figure 3 T-S diagram of the combined gas-steam cycle with afterburner
Source: Cerri

The T-S diagram of the combined gas - vapour cycle with afterburner, starts with the compressor drive by admitting air at atmospheric conditions (1a), increases the pressure and temperature up to (2a), this air is supplied to the combustion chamber, in which the fuel is also injected. Combustion takes place, resulting in high-temperature combustion gases (3a). After combustion, the gases go to the turbine where the transformation of thermal energy to mechanical energy takes place, leaving in conditions (4a), it continues to the afterburner chamber where the thermal energy is increased leaving in (5a), it continues to the heat recuperator where the gases transfer heat to the water, being discharged to the atmosphere (6a).

The liquid that is supplied to the heat recovery unit comes out as superheated steam to enter the steam turbine (3s), after the transformation it comes out as a steam with quality (4s), in the condenser the condensation of this steam is carried out (1s), finally this liquid is propelled towards the heat recovery unit to start the cycle again.

The thermodynamic calculations for this cycle are presented below:

The work and thermal efficiency of the gas turbine is the same as for the combined cycle without post-combustion, therefore, the calculations will no longer be carried out.

Heat recovery steam generator

We define α_{ab} as the ratio of compressed air to fuel used in the afterburner, the final air - fuel mass ratio is:

$$\alpha = \frac{\alpha_{gt} \alpha_{ab}}{\alpha_{gt} + \alpha_{ab}} \tag{21}$$

Which, expressed in stoichiometric ratio and with excess air, is:

$$\alpha = \alpha_{gt} (1 + e) \tag{22}$$

$$\alpha = 14 (1 + 0.06) = 14.84$$

Therefore, the ratio of the afterburner fuel to the fuel in the combustor of the gas turbine is:

$$q = \frac{\alpha_{gt}}{\alpha_{st} (1+e)} - 1 \tag{23}$$

$$q = \frac{54}{14.84} - 1$$

$$q = 2.6388$$

$$q = \frac{\alpha_{gt}}{\alpha_{ab}} \tag{24}$$

$$\alpha_{ab} = \frac{\alpha_{gt}}{q}$$

$$\alpha_{ab} = 20.46$$

The heat balance in the afterburner can be expressed as:

$$(1 + \frac{1}{\alpha}) C_{pa5} T_{5a} = (1 + \frac{1}{\alpha_{gt}}) C_{pa4} T_{4a} + \frac{\Gamma \eta_{bgt}}{\alpha_{gt}}$$

$$T_{5a} = \frac{(1 + \frac{1}{\alpha_{gt}}) C_{pa4} T_{4a} + \frac{\Gamma \eta_{bgt}}{\alpha_{gt}}}{(1 + \frac{1}{\alpha}) C_{pa5}} \tag{25}$$

$$T_{5a} = \frac{(1 + \frac{1}{54})(1.1204)(899.61) + \frac{48490(0.98)}{74.46}}{(1 + \frac{1}{14.84})(1.1204)}$$

$$T_{5a} = 1392.06 K$$

The enthalpy of the steam at the boiler outlet is:

$$H_{3s} = H(T_{3s}, p_{2s})$$

$$T_{3s} = 523 \text{ }^\circ\text{C}$$

$$p_{2s} = 7.742 \text{ Mpa}$$

$$H_{3s} = 3457.87 \text{ KJ/Kg}$$

The enthalpy of the feed water in the condenser is:

$$H_c = h(p_c)$$

$$p_c = 0.00891 \text{ Mpa}$$

$$H_c = 182.46 \text{ KJ/Kg}$$

The energy balance in the steam generator can be expressed as:

$$\left(1 + \frac{1}{\alpha}\right) C_{pa5-6}(T_{5a} - T_{6a})\epsilon_b = S(h_{3s} - h_c)$$

$$\left(1 + \frac{1}{14.84}\right) (1.198)(1392.06 -$$

$$363.60)(0.96) = S(3457.87 - 182.46)$$

$$S = \frac{1262.41}{3275.41}$$

$$S = 0.3854$$

With the

$$p = 7.742 \quad \text{You get} \quad H_{2s} = 1304.53$$

Steam expansion work

The adiabatic efficiency of the steam turbine expansion can be expressed by p_{2s} , p_c and the polytropic efficiency. As $\beta_{st} = p_{2s}/p_c$ the adiabatic efficiency is:

$$\eta_{ast} = \frac{\beta_{st}^{V_s \eta_{pst}} - 1}{\beta_{st}^{V_s} - 1} \beta_{st}^{V_s(1 - \eta_{pst})}$$

$$\beta_{st} = \frac{p_{2s}}{p_c} = \frac{7.742}{8.91} = 868.91$$

$$V_s = \frac{R}{C_p} = \frac{0.4615}{2.1465} = 0.2150$$

$$\eta_{ast} = \left[\frac{868.91^{0.2150(0.86)} - 1}{868.91^{0.2150} - 1} \right] 868.91^{0.2150(1 - 0.86)}$$

$$\eta_{ast} = 0.9312$$

The entropy of the steam at the turbine inlet is:

$$\begin{cases} T = 523 \text{ }^\circ\text{C} \\ P = 7.742 \text{ Kpa} \end{cases} \quad S_{3s} = 6.8149 \text{ KJ/Kg K}$$

The final state of the isentropic expansion is:

$$H_{cs} = H(S_{3s}, p_c)$$

$$x = \frac{6.8149 - 0.61515}{7.5821} = 0.8176$$

$$H_{cs} = H_f + x H_{fg}$$

$$H_{cs} = 2143.88 \text{ KJ/Kg}$$

$$h_{4a} = 3457.87 - (3457.87 - 2143.88)0.93$$

$$h_{4a} = 2227.32 \text{ KJ/Kg}$$

Steam turbine work

$$W_{st} = S(H_{3s} - h_{4s})\eta_{ast}\eta_{mst}$$

$$W_{st} = 0.3854(3457.87 - 2227.32)(0.9312)(0.98)$$

$$W_{st} = 432.79 \text{ KJ/Kg}$$

Heat supplied

$$Q_s = S(H_{3s} - h_c)$$

$$Q_s = 0.3854(3257.87 - 182.46)$$

$$Q_s = 1262.34 \text{ KJ/Kg}$$

Steam and gas turbine thermal efficiency:

$$\eta_{gt} = \frac{W_{tg} - W_c}{Q_s}$$

$$\eta_{gt} = \frac{297.80}{880}$$

$$\eta_{gt} = 0.3384 = 33.84 \%$$

$$\eta_{st} = \frac{W_{st}}{Q_s}$$

$$\eta_{st} = \frac{432.79}{1262.34}$$

$$\eta_{st} = 0.3428 = 34.28 \%$$

Thermal efficiency of the combined cycle:

$$\eta_{CC} = (\eta_{tg} + \eta_{ts}) - \eta_{tg} \eta_{ts}$$

$$\eta_{CC} = (0.3384 + 0.3428) - (0.3384)(0.3428)$$

$$\eta_{CC} = 0.5652 = \mathbf{56.52\%}$$

The following table compares the combined gas-steam cycles without and with afterburners.

Combined Cycle	Wc	Wgt	Wst	Wcc	η_{CC}
Without Post Combustion	473.08	770.88	212.09	509.89	54.6
With afterburner	473.08	770.88	435.25	773.05	54.6

Table 1 Comparative table of work in (KJ/Kg) and thermal efficiency in (%) for the combined cycles with and without afterburner

Source: Own Elaboration

Conclusions and Results

Combined gas-steam cycles for power generation are of great interest, due to the high efficiency that can be obtained. In this research work, a comparison of a combined gas-steam cycle without and with post-combustion was carried out, where the advantage of adding a complementary combustion system before the heat recovery system was determined, obtaining the following results:

For the case of the cycle without post-combustion:

$$W_c = 473.08 \text{ KJ/Kg}$$

$$W_{gt} = 770.88 \text{ KJ/Kg}$$

$$W_{st} = 212.09 \text{ KJ/Kg}$$

$$W_{CC} = 509.89 \text{ KJ/Kg}$$

$$\eta_{CC} = 0.5465 = 54.65\%$$

For the case of the afterburner cycle:

$$W_c = 473.08 \text{ KJ/Kg}$$

$$W_{gt} = 770.88 \text{ KJ/Kg}$$

$$W_{st} = 435.25 \text{ KJ/Kg}$$

$$W_{CC} = 773.05 \text{ KJ/Kg}$$

$$\eta_{CC} = 0.5465 = 54.65\%$$

These results indicate that when using post-combustion in a combined gas-steam cycle as in this case study, the only variation that exists is in the steam turbine due to the difference in the steam-air mass ratios.

References

Aschener, F. S. (1972). The Optimal Choice of Heat Engines for Power Plants of 10 MW to 250 MW Electric Output. Israel Journal of Technology, Vol. 10, No. 4, pp. 223 – 231.

Carmona Contrera, S.A. (2008). Estudio de controladores de ciclo combinado para el mejoramiento de la respuesta dinámica de la unidad. Pontificia Universidad Católica de Chile. Santiago de Chile. Tesis Maestría.

Cerri, G., (1987). “Parametric Analysis of Combined Gas Steam Cycles”, Journal of Engineering for Gas Turbines and Power, vol 109. 46-54.

Cerri, G., (2015). “Parametric Analysis of Combined Gas Steam Cycles”, ASME Paper No. 82-GT-95.

Fraize, W. E., and Kinney, C., (1979). Effects of Steam Injection on the Performance of Gas Turbine Power Cycles. “ASME Journal of Engineering for Power, Vol. 101, pp. 217-227.

Hernández-Fernández, N. J., Zumalacárregui-de Cárdenas, L., & Perez-Ones, O. (2020). Simulación de condiciones de operación y fluidos de trabajo para ciclos Rankine orgánicos. Revista de investigación, Desarrollo e Innovación, 10(2).

Jassim, R. K., Zaki, G.M., Alhazmy, M.M., (2010). Thermo – Economic analysis of a gas turbine power plant with cooled air intake, Yanbu Journal of Engineering and Science.

Kakaras, E, Doukelis, A., Prelipceanu, A., Karellas, S., (2006). Inlet air cooling Methods for gas turbine based power plants, Journal of Engineering for Gas Turbines and Power, Vol. 128,312-317.

Kehlhofer R (1997). Combined cycle Gas and steam Turbine power Plant pennwell publishing company ISBN-0-87814-736-5.

- L. J. Nayak, D. Mahto. (2014). Parametric Analysis of Combined Cycle Power Plant Using Inlet Vapour Compression Cycle. *International Journal of Emerging Technology and Advanced Engineering*.
- Mendoza Nalvarte, J. (2002). Análisis del diseño termodinámico de centrales eléctricas de ciclo combinado. Repositorio Institucional de la Universidad de Piura. Tesis de Licenciatura.
- Nag P.K. (2009). Power Plant Engineering. Tata McGraw-Hill Publishing company limited. New Delhi ISBN-13: 978-0-07-064815- 9.
- Olguin Mejia, A. (2010). Optimización de la planta de ciclo combinado Tula: Sustitución de las calderas de recuperación de calor. Repositorio Institucional UNAM. México. Tesis de Maestría.
- Ondryas, I.S., Wilson, D. A., Kawamoto, M., Haub G.L., (1991). Option in gas Turbine power augmentation using inlet air chilling, *engineering gas turbine and power*, ASME 113 203-2012
- Pfenninger, H., (1982). "Combined steam and gas turbine power stations, Brown Boveri, Paper No. CH-T 040013E
- Quiñones Gutierrez, E. M., & Saldaña Castillo, E. A. (2020). Diseño de una central termoeléctrica de cogeneración de 5 MW para la planta Backus-Motupe.
- Sanjay (2013), Energy and exergy analysis of combined cycle systems with different bottoming cycle configurations, *Int J. Energy Res.* 37: 899-912.
- Sanjay, Onkar Singh, B N Prasad, (2008). Influence of different means of Turbine blade cooling on thermodynamic performance of combined cycle, *Applied thermal Engineering* 28 2315-2326.
- Santos, A.P., (2012). Analysis of gas Turbine Performance with inlet air Cooling techniques, applied to Braziliansites, *J. Aerospace. Technol Manag.* Vol. 4. No. 3, pp.314-353.
- Sonneuschain, H., (1982). A Modular Optimizing Calculation Method of Power Station Energy Balance and Plant Efficiency. "ASME Journal of Engineering of Power, Vol. 104, pp. 225 – 259
- Subugal Garcia, S., & Gomez Moñux, F. (2006). Centrales Térmicas de Ciclo combinado: Teoría y Proyecto. Fernández: Díaz de Santos.
- Tomlinson, L. O. and George, R. L., (1981). Scelta di una turbina a gas e di un ciclo a vapore per il Massimo rendimento di un ciclo combinato. *Nuovo pignone, Energia totale dalle Turbine a Gas, Firenze.* pp. 1-9.
- Wunsch A. (1978). Centrales combinees a turbines a gaz et a vapeur. Situation actuelle et développements futurs, "Rev. Brown Boveri, Vol. 65, No. 10, Oct, pp. 646-655.
- Yadav R (2004) steam and gas turbine and Power plant Engineering. Central publishing House, Allahabad.

Rupture voltage in mineral oil using the megger OTS 60pb equipment to determine its quality and use in transformers

Tensión de ruptura en aceite mineral empleando el equipo megger OTS 60pb para determinar su calidad y utilizarse en transformadores

ESCAMILLA-RODRÍGUEZ, Frumencio*†, LAGUNA-CAMACHO, Juan Rodrigo, RÍOS-HERNÁNDEZ, Sara Anahí and JIMÉNEZ-CRISTÓBAL, Juan Daniel

Facultad de Ingeniería Mecánica y Eléctrica de la Universidad Veracruzana Región Poza Rica – Tuxpan

ID 1st Autor: *Frumencio, Escamilla-Rodriguez* / ORC ID: 0000-0002-5075-1924, CVU CONACYT ID: 1134105

ID 1st Coautor: *Juan Rodrigo, Laguna-Camacho* / ORC ID: 0000-0003-0974-5204

ID 2nd Coautor: *Sara Anahí, Rios-Hernandez* / ORC ID: 0000-0002-2531-0342, CVU CONACYT ID: 1134110

ID 3rd Coautor: *Juan Daniel, Jiménez-Cristóbal* / ORC ID: 0000-0002-9289-6806, CVU CONACYT ID: 1134107

DOI: 10.35429/JOES.2021.24.8.25.32

Received 09 March, 2021; Accepted 28 June, 2021

Abstract

In this project some practices of mineral oil were made to determine the quality for its application in the electrical industry. Then the practices were developed in the laboratory of the Faculty of Mechanical and Electrical Engineering at Universidad Veracruzana using the Megger OTS 60 PB equipment, according to the current IEC 60156 and ASTM D1816 standards, new oil was used in a first analysis which proved to be of correct quality according to the standard, In the second case, oil polluted by the environment was used and it was of less quality since it did not pass the test according to the standard, and finally, degraded oil was used, which was less quality (15°C) and heat was supplied up to 40°C, taking readings at 40°C, 35°C, 30°C and 25°C, giving favorable results due to the influence of the temperature on the mineral oil. In conclusion, according to the results of the test and the comparison with the parameters of the standards, the OTS60PB equipment operates correctly and the results of the equipment are reliable and it can be recommended that mineral oil can be used in transformers.

Quality, Mineral oil, Rupture Voltage

Resumen

En este trabajo se realizaron algunas prácticas de aceite mineral para determinar su calidad para su aplicación en la industria eléctrica. Las practicas se desarrollaron en el laboratorio de la Facultad de Ingeniería Mecánica y Eléctrica de la Universidad Veracruzana utilizando el Equipo Megger OTS 60 PB, de acuerdo a lo establecido con la normatividad vigente IEC 60156 y la ASTM D1816, se empleó aceite nuevo en un primer análisis que resulto ser de calidad correcta de acuerdo a la norma, en segundo caso se utilizó aceite contaminado por el medio ambiente y fue de mala calidad puesto que no paso la prueba de acuerdo a la norma y por último se utilizó aceite degradado el cual fue de mala calidad (15°C) y se le suministro calor hasta los 40°C, tomando lecturas en 40°C, 35°C, 30°C y 25°C, dando resultados favorables por la influencia de la temperatura en el aceite mineral. En conclusión, de acuerdo a los resultados de las prácticas y a la confrontación con los parámetros de las normas, el equipo OTS60PB opera correctamente y los resultados del equipo son confiables y se puede recomendar que el aceite mineral puede ser empleado en transformadores.

Calidad, Aceite mineral, Tensión de ruptura

Citation: ESCAMILLA-RODRÍGUEZ, Frumencio, LAGUNA-CAMACHO, Juan Rodrigo, RÍOS-HERNÁNDEZ, Sara Anahí and JIMÉNEZ-CRISTÓBAL, Juan Daniel. Rupture voltage in mineral oil using the megger OTS 60pb equipment to determine its quality and use in transformers. Journal of Experimental Systems. 2021. 8-24: 25-32

* Correspondence to Author (e-mail: fescamilla@uv.mx).

†Researcher contributing as first Author.

Introduction

One of the problems faced by energy transformation equipment, as is the case of transformers used in CFE, is the cooling or insulation medium by means of gas or oil. In the case of oil, it is necessary to characterize it and verify its quality in order to use it in transformers, considering its physical and chemical properties and thus conclude whether it is possible to use this oil, as well as to use equipment to measure its dielectric strength. The oil is used as a cooling medium and when it comes into contact with solid elements such as the transformer core, it degrades and it is not possible to maintain the insulation oil in optimal conditions for the proper operation of power transformers.

This has led to the development of different physical, chemical and electrical tests that set the parameters of the oil characteristics and as a whole offer a diagnosis of the oil quality for the proper operation of the transformer. Taking into account this background, the research will allow verifying the quality of the oil with the parameters obtained when performing dielectric strength tests.

Justification

The insulating fluid that has the greatest use in electrical equipment is mineral oil, it fulfills the function of electrical insulation and cooling, this is due to its slow degradation period. It is important to know in time the quality of the fluid (mineral oil) to protect the electrical equipment in a power system.

The realization of this work is due to the scarce information on the dielectric strength test in the books that refer to the analysis of power systems. Most of them deal with electrical equipment testing in a general way and not with all the elements that make up an electrical equipment. This work will be of great support to the students of electrical engineering since the results of the practices of dielectric strength of mineral oil developed in the laboratory of FIME Poza Rica, Veracruz, are presented.

Scope

The evaluation of new mineral oil, in service and contaminated by the environment or degraded by means of the dielectric strength test with the Megger OTS60PB equipment of the FIME Poza Rica Laboratory of the Universidad Veracruzana is proposed, presenting the results of the tests developed as laboratory practices. Therefore, the design and construction of transformers is not considered, only the quality of the insulating fluid (oil) is evaluated, giving a recommendation according to the results.

Considerations of IEC 60156 and ASTM D1816 standards for testing

IEC 60156 recommends using a separate test cup for each type of insulating fluid to be tested. Fill them cover them then store them in a dry place. ASTM offers an alternative option of storing the empty beakers in a dust-free cabinet. Immediately prior to testing, those stored full should be emptied and then all surfaces, including the electrodes, should be rinsed with fluid taken from the same sample to be tested. The beaker should then be emptied again and carefully filled with the test sample, taking particular care to avoid the formation of bubbles. If the beaker was stored empty, or if it is to be used for a different fluid than that used for filling during storage, it should be cleaned with a suitable solvent prior to the rinsing and filling procedures described above.

ASTM D1816 specifies the use of a dry hydrocarbon solvent such as kerosene. Do not use solvents with a low boiling point, as they evaporate quickly, cooling the vessel and creating the risk of condensation. Commonly used solvents include acetone. Use clean, lint-free rags to clean the vessel. Avoid touching the electrodes inside during cleaning, and check that they are free of pits or scratches that can cause breakdown voltage values to be reduced.

Methodology for the development of the mineral oil practices

Pour the oil sample. The cleaning methods detailed in the national specifications for oil testing must be followed. Rinse the container with part of the oil sample.

The sample should be poured into the container, avoiding the formation of air bubbles, up to the 500 ml level mark. (Cover the test container when transferring the oil from the filling area to the oil test assembly to avoid contamination).

1. Clean the electrodes and all surrounding parts that come in contact with the oil sample to be tested.

It is recommended to flush with a portion of the oil sample prior to final filling with the oil to be tested. This may be convenient to allow the oil to stop dripping from the electrodes before removing the oil container after opening the door. This will reduce the need to clean the floor of the test chamber.

2. Set the spacing between the electrodes according to the requirement of the test specification undertaken.

The OTS 60PB is a 0 - 60 kV portable dielectric oil tester. Its size and weight make it suitable for on-site evaluation of insulating oil quality.



Figure 1 Schematic of an OTS60PB 70°C dielectric strength meter with a measurement range of 60 kV and a scale division of 1 kV

The dielectric strength test is performed to determine the quality of the mineral oil and a chemical property pH or degree of acidity of the oil. In this study only the dielectric strength test will be carried out with the OTS 60PB equipment.

This equipment is user friendly and shows on screen the type of test to be selected according to the standard as shown in Table 1.

VDE 0370	AS 1767
BS 148	ASTM D877
BS 5730 ^a	ASTM D1816
BS 5730a LEPLC	CEI 10-1
BS 5874	ГОСТ 6581
IEC 60156	IP 295
IEC 156	NFC 27-221
WITHSTAND	SABS 555
5-minute test	UNE 21
Self-check	

Table 1 Table of standards available for the equipment
Source: Prepared by the team

3. Select the desired option and proceed as indicated in the following instructions on the screen fig. 2.

OPTIONS	
BS 148: 1984	
BS 5730 a: 1979	
BA 5874: 1980	
IEC 156: 1973	
▲▼	SELECT

Figure 2 Sample menu screen

Dielectric strength of oil

The dielectric strength of the oil is defined by the breakdown voltage or dielectric strength test. The exact method of performing the test is defined by the standard being used. The standard generally defines parameters such as the voltage value, the shape and size of the electrodes, the electrode spacing, the rate of rise of the test voltage, the number of times the test is repeated and whether the oil is agitated during the test.

Standards for breakdown voltage values in insulating oil testing

From the "Megger's Guide to Dielectric Breakdown Testing of Insulating Oils" we can take the following:

ASTM D877 standard the IEEE recommends it only for acceptance testing of new oil received from a supplier, either in bulk loads or containers, to ensure that the oil was properly stored and transported.

In these cases, a breakdown voltage value of 30 kV or more is generally considered acceptable, while values below 25 kV are considered unacceptable. Values between 25 and 30 kV are considered questionable. For new oil, a minimum value of 30 kV.

Use of disk-shaped electrodes with 25.4 mm (1 in.) diameter and at least 3.18 mm (0.125 in.) thickness. These electrodes are made of polished bronze and are mounted so as to have their faces parallel and horizontally in line on the test vessel. It is specified that the edges should be sharp, with a radius of not more than 0.010 in (0.254 mm).

ASTM D1816 is more sensitive than D877 to moisture, aging and oxidation of the oil, and is more affected by the presence of particles in the oil.

Specifies the use of 36 mm diameter mushroom-shaped electrodes. The electrodes are made of bronze and must be polished and free of pickling, scratches, pitting or carbon build-up. The oil is agitated during the test sequence by a motor-driven two-vane impeller. The standard prescribes the impeller dimensions and pitch, as well as the operating speed, which must be between 200 rpm and 300 rpm.

This method is very sensitive to dissolved gases. Excessive amounts of gas in the oil can lower the test results to the point that suitable oil samples with low moisture and particulate content will fail this test. It is important to keep this in mind when testing small insulated transformer oils in gas atmospheres and, in some cases, free-breathing transformers.

IEC 60156 is an international standard that appears in various forms, as IEC national member committees in several countries have adopted it.


Standard test	IEC156, EN60156, AS 1767, BS 5730, IP 295, NFC 27, SABS 555 y UNE 21
Electrode shape	
Electrode spacing	2.5 mm

Table 2 Comparative table of European standards

The IEC standard differs in several points from D1816, but the main difference is that the IEC standard allows the optional use of an impeller for agitation, the use of a magnetic ball stirrer or no agitation. The standard specifies that no statistically significant differences have been found between tests with or without shaking. The use of a magnetic stirrer is allowed only when there is no risk of removing magnetic particles from the oil sample under test.

When the oil is used as a coolant and therefore when circulating it, it will be agitated during the test. For example, oil from a transformer is normally circulated if it is used as a coolant, so an oil sample taken in this case will normally be agitated to ensure the best chance of detecting particulate contamination.

Circuit breaker oil is normally used statically so particles will naturally fall to the bottom where they are unlikely to cause problems. So in static applications an oil sample will not be agitated. The dielectric breakdown values of the IEC 60156 method are usually higher than those of the ASTM methods.

Possibly this is due in part to differences in ramp-up rate and electrode spacing when compared to D1816, and electrode shape when compared to D877. (The IEC electrode shape provides a more uniform electric field). The result is that for well-maintained transformers the breakdown voltages may be higher than the 60 kV that the test instrument can reach. This may not be a problem when evaluating new oil from a supplier, or even oil in use, but often an actual breakdown voltage value is required. When testing with IEC 60156, therefore, it is advisable to use an instrument capable of applying a higher voltage. As with D1816, dissolved gas in the oil sample can reduce breakdown values, but the effect is much less pronounced than with IEC 60156.

Using the IEC 60156 test method 30 kV or more. Oil that has been vacuum filtered in a laboratory must have a minimum dielectric breakdown voltage of 70 kV.

Dielectric strength test of mineral oil

A series of new oil practices were carried out to determine its quality under the following protocol:

- a. Take oil temperature and ambient humidity.
- b. Wash the cup with part of the sample. Fill the cup with another portion of the sample up to the 500 ml mark. Place it in the test equipment.
- c. Press the power button on the test equipment, let it stand for 2 min.
- d. Select the test standard on the screen, once selected press the start button.

- e. Take data of each rupture and at the end of the test take data of the mean and standard deviation if required by the standard.
- f. Remove the cup from the equipment
- g. Verify the results according to the standard.
- h. Give diagnosis according to the standard
- i. See sequence of standards

First practice with the UNE 21- 309- 89 standard

New mineral oil was considered as the first case. Two practices were carried out under the UNE 21 standard, where the humidity and temperature conditions are shown in tables, as well as the results of the breakdown voltage readings. The practice starts according to the protocol for the beginning of the test, the sequence is as follows.

Temp		Humidity		Date	
28 °C		80%		16/10/2019	
	kV	LS	LI	Media	Ds
1	54	65	53	59	2%
2	60				
3	60				
4	57				
5	58				
6	60				

Table 3 Results of practice No. 1 UNE 21 standard
Source: Own Elaboration

Temp		Humidity		Date	
28 °C		80%		16/10/2019	
	Kv	Ls	Li	Media	Ds
1	58	633	51	577	4%
2	54				
3	60				
4	56				
5	57				
6	59				

Table 4 Results of practice No. 2. UNE 21 Standard
Source: Own Elaboration

Practices 3 and 4 were performed under BS 148, where humidity and temperature conditions are shown in tables, as well as the results of the breakdown voltage readings. A sample of the same transformer is used and the practice is carried out according to the test start protocol. This standard has a "pass/fail" option and displays the six results, the average and indicates whether the oil is of the correct quality.

Temp	Humidity	Date
26°C	67%	18/10/2019
	kV	Media
1	47	56
2	60	
3	60	
4	51	
5	60	
6	55	


Table 5 Results of practice No. 3. BS 148 Standard
Source: Own Elaboration

Temp	Humidity	Date
26 °C	67%	18/10/2019
	kV	Media
1	47	53
2	59	
3	60	
4	60	
5	57	
6	31	


Table 6 Results of practice No. 4. BS 148 Standard
Source: Own Elaboration

Results

The results obtained are compared below. First, the results of the practices are validated and then compared with the parameters established by the regulations in order to verify if the oil complies with the established stress ranges. Graphs 1 and 2 show the results of the UNE 21 test.




Graph 1 UNE 21 Practice 1. This test is within the parameters of the IEC 60156 standard, because the standard deviation does not exceed 4% of the upper and lower limits
Source: Own Elaboration



Graph 2 UNE 21 Práctica 2. Esta prueba está dentro de los parámetros de la norma IEC 60156, porque la desviación estándar no pasa del 3% del límite superior e inferior


Source: Own Elaboration

Graphs 3 and 4 show the results of practices 3 and 4 BS 148



Graph 3 BS 148 Practice 3. Result of oil in service that also complies with the parameters of the standard

Source: Own Elaboration



Graph 4 BS 148 practice 4. Result of oil in service that also complies with the parameters of the standard

Source: Own Elaboration

In this second case, four tests were carried out and all were found to be of incorrect quality. This was under BS 148, where the humidity and temperature conditions are shown in tables, as well as the results of the breakdown voltage readings.

A few samples of contaminated oil are used and the practice is carried out according to the protocol. This standard has a "pass/fail" option and shows the 6 results, the mean and the result of the mineral oil condition.

Temperature	26 °C
Humidity	66%
Wind	11 km/hr
Deviation	S= 1.366
standard deviation	$S/\bar{x} = 0.132$
Dielectric Capacity	
1	9 kV
2	12 kV
3	9 kV
4	12 kV
5	10 kV
6	10 kV
Average voltage: 10 Kv	

Table 7 Results of practice No. 5. BS 148 Standard


Source: Own Elaboration

The four practices were then analyzed as a whole using a comparative matrix and the results were plotted.

	Practice 5	Practice 6	Practice 7	Practice 8
1	9	11	21	12
2	12	14	17	13
3	9	13	24	9
4	12	10	17	13
5	10	10	15	9
6	10	17	15	13
Average voltage	10 kV	13 kV	18 kV	12 kV

Table 8 Dielectric strength results

Source: Own Elaboration



Graph 5 Dielectric strength

Source: Own Elaboration

Graph 5 shows the variation of the dielectric strength of practices 5, 6, 7 and 8 considered oil A, oil B, oil C and oil D respectively of which oil C test can be considered of adequate quality due to its breakdown voltage.




Finally, a practice 9 was performed on another degraded mineral oil to observe its behavior with or without heat supply. This oil did not pass the UNE 21 test (5 minutes) under normal conditions (15°C) and it was decided to supply it with heat, performing the practice again. This was done by increasing its temperature by 5 degrees, therefore, the following temperature readings were considered, 25°C, 30°C, 35°C and 40°C. As the oil cooled very quickly, the first reading was 40°C and subsequently 35°C, 30°C and 25°C, giving results that we can observe in the following table, to a certain extent expected, because the amount of humidity was decreased.

	Oil 15°C	Oil 25°C	Oil 30°C	Oil 35°C	Oil 40°C
1	10	42	54	39	41
2	10	50	52	60	48
3	9	35	50	50	40
1	10	42	54	39	41
Average voltage	10kV	42 kV	52 kV	50kV	43kV

Table 9 Results of practice 9 of mineral oil at different temperatures

Source: Own Elaboration

Annexes

Standard test	EN60156 AS 1767 BS 5730 IEC156 IP 295 NFC 27 SABS 555 UNE 21	CEI 10-1 TOCT 6581 VDE 0370 SATS 286 AS1767	ASTM D1816
Electrode shape			
Electrode spacing	2.5 mm		2.0 mm

Annex 1 Test specification and different types of electrodes

Valid test conditions	
ASTM D 877	
Procedure A	Procedure A
Tests should be repeated if the range of recorded breakdown voltages is more than 92% of the mean. If the range of 10 breakdown voltages is more than 151% the cause should be investigated.	
ASTM 1816	
If the rupture does not occur at 2 mm, reduce the distance to 1 mm. distance to 1 mm. Tests must be repeated if the range of breakdown voltages recorded is more than 120% of average at 1 mm electrode spacing and 92% of the average with 2 mm electrode spacing. electrode spacing of 2 mm.	
IEC 60156	
Expected range of the standard deviation to mean ratio as a function of the mean is provided as a graph. standard deviation to mean as a function of the mean is provided as a graph.	

Annex 2 Validation of the test in the different standards

Oil in service Equipment voltage	Dielectric breakdown voltage		
	Well	Acceptable	Poor
≥ 72.5 kV	> 40kV	30-40 kV	> 30 kV
≥ 72.5 kV ≥ 170kV	> 50 kV	40-50 kV	> 30 kV
> 270 kV	> 60 kV	50 - 60 kV	> 50 kV

Annex 3 Breakdown voltage for oil in service IEC 60156

ASTM D 877 Method		
Acceptable	Dudoso	Unacceptable
≥ 30 kV	< 32 a 28 ≥ 25 kV	< 25 kV

Annex 4 Voltage range per ASTM D 877 standard

Acknowledgements

I would like to thank the School of Mechanical and Electrical Engineering, Poza Rica - Tuxpan area of the Universidad Veracruzana, for the facilities provided for the preparation of this article.

Conclusions

After analyzing the results of the mineral oil breaking strain, we can conclude the following: The practices carried out under the UNE 21 standard, are within the parameters of the standard. No result exceeds 10% of the mean value, therefore the result is valid. According to the parameters of the standard, the oil is in good condition for use. When applying BS 148, which gives the pass/fail option in practices 3 and 4, where oil in service was used, it was found that the two samples comply with the standard, since the screen of the equipment shows the result when applying this standard (pass/fail). For practice 5, contaminated oil was used under BS 148, the result fails, as well as practices 6, 7 and 8.

For practice 9, the oil used in practices 5, 6, 7 and 8 was used again and when heat was supplied to it, the breaking strain of the oil improved considerably. According to the results of the practices and the confrontation of results with the parameters of the standards, the OTS60PB equipment operates correctly and it was concluded that all results of the operation of the equipment are reliable, that the instructions for handling the oil samples must be followed, since any contamination, no matter how small, can negatively affect the test results, thus generating an erroneous diagnosis of the oil conditions.

References

CFE. (2003). *Manual de procedimientos de prueba de campo para equipo de subestaciones de distribución*. México, D.F.: CFE SDD.

Jorge Luis Ceballos Sánchez, Ernesto García Maldonado (2013). “*Análisis Técnico del líquido contenido como Refrigerante y aislante en Transformadores*”. Tesis (Ingeniero Electricista). Instituto Politécnico Nacional.

Megger Limited Archcliffe Road Dover. (2003). *La guía de Megger sobre las pruebas de ruptura dieléctrica de aceites de aislamiento*. España.

Norma ASTM D181 (por sus siglas in ingles American Society for Testing and Materials)

Norma IEC 60156 (por sus siglas en ingles International Electrotechnical Commission)

Porragas Beltrán, L. H. (2009). *Manual de Prácticas del Laboratorio de Máquinas Eléctricas*. Veracruz, Veracruz, México.

TRAFO ELETTRIO SRL. (2015). *TRAFO ELETTRIO*. From <http://www.trafoelettrio.com/esp/aceite.html>

Víctor Martínez García (1985). “*Fabricación y usos de los Aceites Lubricantes*”. Tesis (Ingeniero Químico Industrial) Instituto Politécnico Nacional. <https://es.scribd.com/document/342706827/Aceites-Minerales-Aislantes-Para-Transformadores-y-Aparamenta-de-Conexión>

Instructions for Scientific, Technological and Innovation Publication

[Title in Times New Roman and Bold No. 14 in English and Spanish]

Surname (IN UPPERCASE), Name 1st Author†*, Surname (IN UPPERCASE), Name 1st Coauthor, Surname (IN UPPERCASE), Name 2nd Coauthor and Surname (IN UPPERCASE), Name 3rd Coauthor

Institutional Affiliation of Author including Dependency (No.10 Times New Roman and Italic)

International Identification of Science - Technology and Innovation

ID 1st Author: (ORC ID - Researcher ID Thomson, arXiv Author ID - PubMed Author ID - Open ID) and CVU 1st author: (Scholar-PNPC or SNI-CONACYT) (No.10 Times New Roman)

ID 1st Coauthor: (ORC ID - Researcher ID Thomson, arXiv Author ID - PubMed Author ID - Open ID) and CVU 1st coauthor: (Scholar or SNI) (No.10 Times New Roman)

ID 2nd Coauthor: (ORC ID - Researcher ID Thomson, arXiv Author ID - PubMed Author ID - Open ID) and CVU 2nd coauthor: (Scholar or SNI) (No.10 Times New Roman)

ID 3rd Coauthor: (ORC ID - Researcher ID Thomson, arXiv Author ID - PubMed Author ID - Open ID) and CVU 3rd coauthor: (Scholar or SNI) (No.10 Times New Roman)

(Report Submission Date: Month, Day, and Year); Accepted (Insert date of Acceptance: Use Only ECORFAN)

Abstract (In English, 150-200 words)

Objectives
Methodology
Contribution

Keywords (In English)

Indicate 3 keywords in Times New Roman and Bold No. 10

Abstract (In Spanish, 150-200 words)

Objectives
Methodology
Contribution

Keywords (In Spanish)

Indicate 3 keywords in Times New Roman and Bold No. 10

Citation: Surname (IN UPPERCASE), Name 1st Author, Surname (IN UPPERCASE), Name 1st Coauthor, Surname (IN UPPERCASE), Name 2nd Coauthor and Surname (IN UPPERCASE), Name 3rd Coauthor. Paper Title. Journal of Experimental Systems. Year 1-1: 1-11 [Times New Roman No.10]

* Correspondence to Author (example@example.org)

† Researcher contributing as first author.

Introduction

Text in Times New Roman No.12, single space.

General explanation of the subject and explain why it is important.

What is your added value with respect to other techniques?

Clearly focus each of its features

Clearly explain the problem to be solved and the central hypothesis.

Explanation of sections Article.

Development of headings and subheadings of the article with subsequent numbers


[Title No.12 in Times New Roman, single spaced and bold]

Products in development No.12 Times New Roman, single spaced.

Including graphs, figures and tables-Editable

In the article content any graphic, table and figure should be editable formats that can change size, type and number of letter, for the purposes of edition, these must be high quality, not pixelated and should be noticeable even reducing image scale.

[Indicating the title at the bottom with No.10 and Times New Roman Bold]



Graphic 1 Title and *Source (in italics)*

Should not be images-everything must be editable.




Figure 1 Title and *Source (in italics)*

Should not be images-everything must be editable.

Table 1 Title and *Source (in italics)*

Should not be images-everything must be editable.

Each article shall present separately in **3 folders**:
a) Figures, b) Charts and c) Tables in .JPG format, indicating the number and sequential Bold Title.

For the use of equations, noted as follows:

$$Y_{ij} = \alpha + \sum_{h=1}^r \beta_h X_{hij} + u_j + e_{ij} \quad (1)$$

Must be editable and number aligned on the right side.

Methodology

Develop give the meaning of the variables in linear writing and important is the comparison of the used criteria.

Results

The results shall be by section of the article.

Annexes

Tables and adequate sources

Thanks

Indicate if they were financed by any institution, University or company.

Conclusions

Explain clearly the results and possibilities of improvement.

Instructions for Scientific, Technological and Innovation Publication

References

Use APA system. Should not be numbered, nor with bullets, however if necessary numbering will be because reference or mention is made somewhere in the Article.

Use Roman Alphabet, all references you have used must be in the Roman Alphabet, even if you have quoted an Article, book in any of the official languages of the United Nations (English, French, German, Chinese, Russian, Portuguese, Italian, Spanish, Arabic), you must write the reference in Roman script and not in any of the official languages.

Technical Specifications

Each article must submit your dates into a Word document (.docx):

Journal Name

Article title

Abstract

Keywords

Article sections, for example:

1. Introduction

2. Description of the method

3. Analysis from the regression demand curve

4. Results

5. Thanks

6. Conclusions

7. References

Author Name (s)

Email Correspondence to Author

References

Intellectual Property Requirements for editing:

-Authentic Signature in Color of Originality Format Author and Coauthors

-Authentic Signature in Color of the Acceptance Format of Author and Coauthors

Reservation to Editorial Policy

Journal of Experimental Systems reserves the right to make editorial changes required to adapt the Articles to the Editorial Policy of the Research Journal. Once the Article is accepted in its final version, the Research Journal will send the author the proofs for review. ECORFAN® will only accept the correction of errata and errors or omissions arising from the editing process of the Research Journal, reserving in full the copyrights and content dissemination. No deletions, substitutions or additions that alter the formation of the Article will be accepted.

Code of Ethics - Good Practices and Declaration of Solution to Editorial Conflicts

Declaration of Originality and unpublished character of the Article, of Authors, on the obtaining of data and interpretation of results, Acknowledgments, Conflict of interests, Assignment of rights and Distribution

The ECORFAN-Mexico, S.C Management claims to Authors of Articles that its content must be original, unpublished and of Scientific, Technological and Innovation content to be submitted for evaluation.

The Authors signing the Article must be the same that have contributed to its conception, realization and development, as well as obtaining the data, interpreting the results, drafting and reviewing it. The Corresponding Author of the proposed Article will request the form that follows.

Article title:

- The sending of an Article to Journal of Experimental Systems emanates the commitment of the author not to submit it simultaneously to the consideration of other series publications for it must complement the Format of Originality for its Article, unless it is rejected by the Arbitration Committee, it may be withdrawn.
- None of the data presented in this article has been plagiarized or invented. The original data are clearly distinguished from those already published. And it is known of the test in PLAGSCAN if a level of plagiarism is detected Positive will not proceed to arbitrate.
- References are cited on which the information contained in the Article is based, as well as theories and data from other previously published Articles.
- The authors sign the Format of Authorization for their Article to be disseminated by means that ECORFAN-Mexico, S.C. In its Holding Bolivia considers pertinent for disclosure and diffusion of its Article its Rights of Work.
- Consent has been obtained from those who have contributed unpublished data obtained through verbal or written communication, and such communication and Authorship are adequately identified.
- The Author and Co-Authors who sign this work have participated in its planning, design and execution, as well as in the interpretation of the results. They also critically reviewed the paper, approved its final version and agreed with its publication.
- No signature responsible for the work has been omitted and the criteria of Scientific Authorization are satisfied.
- The results of this Article have been interpreted objectively. Any results contrary to the point of view of those who sign are exposed and discussed in the Article.

Copyright and Access

The publication of this Article supposes the transfer of the copyright to ECORFAN-Mexico, SC in its Holding Bolivia for its Journal of Experimental Systems, which reserves the right to distribute on the Web the published version of the Article and the making available of the Article in This format supposes for its Authors the fulfilment of what is established in the Law of Science and Technology of the United Mexican States, regarding the obligation to allow access to the results of Scientific Research.

Article Title:

Name and Surnames of the Contact Author and the Coauthors	Signature
1.	
2.	
3.	
4.	

Principles of Ethics and Declaration of Solution to Editorial Conflicts

Editor Responsibilities

The Publisher undertakes to guarantee the confidentiality of the evaluation process, it may not disclose to the Arbitrators the identity of the Authors, nor may it reveal the identity of the Arbitrators at any time.

The Editor assumes the responsibility to properly inform the Author of the stage of the editorial process in which the text is sent, as well as the resolutions of Double-Blind Review.

The Editor should evaluate manuscripts and their intellectual content without distinction of race, gender, sexual orientation, religious beliefs, ethnicity, nationality, or the political philosophy of the Authors.

The Editor and his editing team of ECORFAN® Holdings will not disclose any information about Articles submitted to anyone other than the corresponding Author.

The Editor should make fair and impartial decisions and ensure a fair Double-Blind Review.

Responsibilities of the Editorial Board

The description of the peer review processes is made known by the Editorial Board in order that the Authors know what the evaluation criteria are and will always be willing to justify any controversy in the evaluation process. In case of Plagiarism Detection to the Article the Committee notifies the Authors for Violation to the Right of Scientific, Technological and Innovation Authorization.

Responsibilities of the Arbitration Committee

The Arbitrators undertake to notify about any unethical conduct by the Authors and to indicate all the information that may be reason to reject the publication of the Articles. In addition, they must undertake to keep confidential information related to the Articles they evaluate.

Any manuscript received for your arbitration must be treated as confidential, should not be displayed or discussed with other experts, except with the permission of the Editor.

The Arbitrators must be conducted objectively, any personal criticism of the Author is inappropriate.

The Arbitrators must express their points of view with clarity and with valid arguments that contribute to the Scientific, Technological and Innovation of the Author.

The Arbitrators should not evaluate manuscripts in which they have conflicts of interest and have been notified to the Editor before submitting the Article for Double-Blind Review.

Responsibilities of the Authors

Authors must guarantee that their articles are the product of their original work and that the data has been obtained ethically.

Authors must ensure that they have not been previously published or that they are not considered in another serial publication.

Authors must strictly follow the rules for the publication of Defined Articles by the Editorial Board.

The authors have requested that the text in all its forms be an unethical editorial behavior and is unacceptable, consequently, any manuscript that incurs in plagiarism is eliminated and not considered for publication.

Authors should cite publications that have been influential in the nature of the Article submitted to arbitration.

Information services

Indexation - Bases and Repositories

RESEARCH GATE (Germany)

GOOGLE SCHOLAR (Citation indices-Google)

REDIB (Ibero-American Network of Innovation and Scientific Knowledge- CSIC)

MENDELEY (Bibliographic References Manager)

DULCINEA (Spanish scientific journals)

UNIVERSIA (University Library-Madrid)

SHERPA (University of Nottingham - England)

Publishing Services

Citation and Index Identification H

Management of Originality Format and Authorization

Testing Article with PLAGSCAN

Article Evaluation

Certificate of Double-Blind Review

Article Edition

Web layout

Indexing and Repository

Article Translation

Article Publication

Certificate of Article

Service Billing

Editorial Policy and Management

21 Santa Lucía, CP-5220. Libertadores -Sucre – Bolivia. Phones: +52 1 55 6159 2296, +52 1 55 1260 0355, +52 1 55 6034 9181; Email: contact@ecorfan.org www.ecorfan.org

ECORFAN®

Chief Editor

BARRERO-ROSALES, José Luis. PhD

Executive Director

RAMOS-ESCAMILLA, María. PhD

Editorial Director

PERALTA-CASTRO, Enrique. MSc

Web Designer

ESCAMILLA-BOUCHAN, Imelda. PhD

Web Diagrammer

LUNA-SOTO, Vladimir. PhD

Editorial Assistant

SORIANO-VELASCO, Jesús. BsC

Translator

DÍAZ-OCAMPO, Javier. BsC

Philologist

RAMOS-ARANCIBIA, Alejandra. BsC

Advertising & Sponsorship

(ECORFAN® Bolivia), sponsorships@ecorfan.org

Site Licences

03-2010-032610094200-01-For printed material ,03-2010-031613323600-01-For Electronic material,03-2010-032610105200-01-For Photographic material,03-2010-032610115700-14-For the facts Compilation,04-2010-031613323600-01-For its Web page,19502-For the Iberoamerican and Caribbean Indexation,20-281 HB9-For its indexation in Latin-American in Social Sciences and Humanities,671-For its indexing in Electronic Scientific Journals Spanish and Latin-America,7045008-For its divulgation and edition in the Ministry of Education and Culture-Spain,25409-For its repository in the Biblioteca Universitaria-Madrid,16258-For its indexing in the Dialnet,20589-For its indexing in the edited Journals in the countries of Iberian-America and the Caribbean, 15048-For the international registration of Congress and Colloquiums. financingprograms@ecorfan.org

Management Offices

21 Santa Lucía, CP-5220. Libertadores -Sucre–Bolivia.

Journal of Experimental Systems

“Elaboration of Octagonal Roses to represent the wind patterns in the Port de Veracruz during the last 10 years”

GONZALEZ-JUAREZ Aníbal, AGUILAR-RAMIREZ Ana María, UTRERA-ZARATE, Alberto and MOLINA-NAVARRO, Antonio

Instituto Oceanográfico del Pacífico

“Comparative study between Biological treatment and a physicochemical treatment for the removal of Butyl Acetate in industrial residual effluents”

CARRILLO-CABRERA, Roxana, RODRIGUEZ-MORALES, Jose Alberto, LEDESMA-GARCIA, Janet and AMARO-REYES, Aldo

Universidad Autónoma de Querétaro

“Thermodynamic analysis of a combined gas-steam cycle without and with afterburner”

CASADOS-LÓPEZ, Edzel Jair, CASADOS-SÁNCHEZ, Alvaro, ESCAMILLA-RODRÍGUEZ, Frumencio and CORTÉZ-DOMÍNGUEZ, Cristóbal

Universidad Veracruzana

“Rupture voltage in mineral oil using the megger OTS 60pb equipment to determine its quality and use in transformers”

ESCAMILLA-RODRÍGUEZ, Frumencio, LAGUNA-CAMACHO, Juan Rodrigo, RÍOS-HERNÁNDEZ, Sara Anahí and JIMÉNEZ-CRISTÓBAL, Juan Daniel

Universidad Veracruzana

